



TOPOGRAPHIC SURVEY

PREPARED BY: RRM DESIGN GROUP
DATE: NOVEMBER 10, 2021
PROJECT No.: 1417-05-CU21

DATUM:

HORIZONTAL CONTROL FOR POINTS 8029 & 8026 AS PUBLISHED IN THE CITY OF SAN LUIS OBISPO 2007 HORIZONTAL CONTROL NETWORK. CITY NETWORK IS BASED ON THE NORTH AMERICAN DATUM OF 1983 (NAD83) EPOCH DATE 1991.35, ZONE 5 CALIFORNIA.

VERTICAL CONTROL BENCHMARK NO. 195 WITH AN ELEVATION OF 252.72 L&T 12± WEST OF EASTERLY DRIVE APPROACH TO SHELL STATION AT FOOTHILL & BROAD AS PUBLISHED IN THE CITY OF SAN LUIS OBISPO 2007 BENCHMARK SYSTEM. CITY'S BENCHMARK SYSTEM IS BASED ON THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88).



Know what's below.
Call 811 before you dig.

SHEET SUMMARY

CIVIL:

C-1.1	TITLE SHEET, VICINITY MAP, SHEET SUMMARY
C-1.2	GENERAL NOTES, LEGEND, SHEET INDEX
C-1.3	KEY MAP
C-2.1 TO C-2.2	DEMOLITION PLANS
C-3.1 TO C-3.16	STREETS, SIGNAGE & STRIPPING - PLAN & PROFILES
C-4.1 TO C-4.49	CURB RETURNS
C-5.1 TO C-5.2	DETAILS

ELECTRICAL:

E-0.1	ELECTRICAL NOTES, LEGEND AND SINGLE LINE DIAGRAMS
E-1.1	ELECTRICAL PLAN - BIKE PATH
E-1.2	ELECTRICAL PLAN - CHORRO UNDERPASS

LANDSCAPE:

LP001 TO LP502	PLANTING PLANS AND DETAILS
LI001 TO LI502	IRRIGATION PLANS AND DETAILS

STRUCTURAL:

S-101	SHEET INDEX, LEGEND & ABBREVIATION
S-102	GENERAL NOTES
S-103	SPECIAL INSPECTION & TESTS
S-201	TYPICAL CONCRETE DETAILS
S-211	TYPICAL CONCRETE DETAILS
S-311	RETAINING WALL DETAILS

NOTES:

1. FOR FULL CIVIL SHEET INDEX LIST SEE SHEET C-1.3
2. FOR CIVIL KEY MAP SEE SHEET C-1.3

Reference Documents:
City Standard Specifications - August 2020 Edition
City Engineering Standards - August 2020 Edition



SAN LUIS OBISPO COUNTY, CALIFORNIA

CERRO SAN LUIS GREENWAY



APPROVED BY

Brian A. Nelson, City Engineer R.C.E. C79870 Approved Date

SPECIFICATION NO.

1000036

DATE

JUNE 2, 2022
FILE NO./LOCATION
1417-05-CU21

SHEET

C-1.1

GENERAL NOTES:

1. ALL WORK SHALL BE PERFORMED IN CONFORMANCE WITH THESE PLANS, SPECIAL PROVISIONS PREPARED FOR THIS PROJECT AND THE 2020 CITY OF SAN LUIS OBISPO STANDARD SPECIFICATIONS AND ENGINEERING STANDARDS, IN CONJUNCTION WITH THE STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS AND STANDARD PLANS, 2015 EDITION (UNREVISED), AND LATEST EDITION OF CALIFORNIA MUTCD.
2. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR OR PERMITTEE TO CONTACT "UNDERGROUND SERVICE ALERT OF NORTHERNCENTRAL CALIFORNIA" BY PHONE AT 8-1-1 FORTY-EIGHT (48) HOURS PRIOR TO START OF CONSTRUCTION FOR LOCATION OF POWER, TELEPHONE, OIL AND NATURAL GAS UNDERGROUND FACILITIES. CONTRACTOR OR PERMITTEE SHALL ALSO CONTACT THE APPROPRIATE AGENCY FOR THE LOCATION OF CABLE T.V., WATER, SEWER, DRAINAGE OR UNDERGROUND FACILITIES.
4. THE CONTRACTOR SHALL "POSSESS A CLASS "A" OR "C12" LICENSE AT THE TIME THE BIDS OPEN AND DURING THE ENTIRE LENGTH OF THE CONTRACT.
5. THESE PLANS DO NOT INDICATE ALL EXISTING FACILITIES IN THE VICINITY OF THE PROPOSED WORK SUCH AS EXISTING IRRIGATION HEADS AND LINES, SHRUBBERY AND VEGETATION, ETC. THE CONTRACTOR MUST USE CARE TO AVOID DAMAGE TO ANY EXISTING IMPROVEMENTS OR VEGETATION IN THE VICINITY OF THE WORK, AND MUST REPAIR ANY FACILITIES DAMAGE DURING CONSTRUCTION TO THE SATISFACTION OF THE ENGINEER.
6. WHERE TRIMMING OF EXISTING VEGETATION IS REQUIRED DURING CONSTRUCTION IT MUST BE DONE IN A MANNER TO REMOVE THE MINIMUM POSSIBLE AMOUNT OF VEGETATION AND LEAVE THE REMAINING IN AN ATTRACTIVE CONDITION. CONTRACTOR MUST COORDINATE WITH CITY ARBORIST PRIOR TO TRIMMING OF ANY VEGETATION.
7. PROTECT TREE BRANCHES, TRUNK, ROOTS AND FOLIAGE THROUGH PROPER TRIMMING AND CONSTRUCTION TECHNIQUES WHENEVER POSSIBLE PER CITY STD SECTION 20.
8. THESE PLANS DO NOT INDICATE ALL OVERHEAD LINES. CONTRACTOR SHALL TAKE CARE DURING CONSTRUCTION TO AVOID CONTACT WITH OR DAMAGE TO EXISTING OVERHEAD LINES.
9. ANY EXISTING UTILITIES AND IMPROVEMENTS THAT BECOME DAMAGED DURING CONSTRUCTION SHALL BE COMPLETELY RESTORED TO THE SATISFACTION OF THE ENGINEER AT THE CONTRACTOR'S SOLE EXPENSE.
10. CONTRACTOR SHALL CONTACT ALL UTILITY COMPANIES AND AGENCIES WITH SERVICES IN THE AREA PRIOR TO COMMENCING CONSTRUCTION ACTIVITIES AND COORDINATE WITH THE UTILITY COMPANIES AFFECTED BY CONSTRUCTION.
11. PRIOR TO THE START OF CONSTRUCTION, THE CONTRACTOR'S LICENSED LAND SURVEYOR SHALL FILE A CORNER RECORD IN THE OFFICE OF THE SAN LUIS OBISPO COUNTY SURVEYOR FOR EACH EXISTING MONUMENT WITHIN THE PROJECT AREA THAT HAS THE POTENTIAL TO BE DISTURBED. PROTECT BENCHMARKS AND PROPERTY CORNERS IN PLACE PER CITY STD SECTION 5-1.26.
12. PROTECT SURVEY MONUMENTS IN PLACE DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH THE REPLACEMENT OF DAMAGED OR DISPLACED SURVEY MONUMENTS AND SHALL NOTIFY THE CITY FIVE (5) WORKING DAYS PRIOR TO RESTORING MONUMENTS. MONUMENTS SHALL BE RESET BY A CALIFORNIA LICENSED LAND SURVEYOR AND SHALL INCLUDE PREPARING AND FILING A CORNER RECORD WITH SAN LUIS OBISPO COUNTY.
13. ALL STRIPING AND MARKINGS SHALL BE PER CALTRANS REVISED STANDARD PLANS 2015 -A20A, A20B, A20C, A20D, A24A, A24B, A24C, A24D, AND A24E. ANY STRIPING NOT MARKED FOR REMOVAL SHALL BE PROTECTED IN PLACE. SEE SPECIAL PROVISIONS SECTION 64.
14. ALL CURB, GUTTER, AND SIDEWALK IMPROVEMENTS SHALL BE COMPLETED PRIOR TO THE START OF PAVING WORK.
15. CONCRETE SIDEWALKS MUST CONFORM TO ENGINEERING STANDARDS 4110 & 4220.
16. REMOVAL AND REPLACEMENT OF EXISTING CONCRETE SHALL CONFORM TO ENGINEERING STANDARD 4910.
17. ALL PAVEMENT MARKINGS, STRIPING, AND SIGN LOCATIONS SHALL BE APPROVED BY THE CITY PRIOR TO INSTALLATION.
18. ALL EQUIPMENT SUBMITTALS, INCLUDING PATH/STREET LIGHTING, SIGNS, GREEN BIKE LANE COATING, ETC. SHALL BE APPROVED BY CITY PRIOR TO INSTALLATION.
19. WHERE NO CURB AND GUTTER EXISTS AND EDGE OF PAVEMENT IS OBSTRUCTED BY VEGETATION, CONTRACTOR SHALL TRIM BACK VEGETATION TO REVEAL EDGE OF PAVEMENT PRIOR TO IMPROVEMENTS.
20. GREEN PAINT AT BIKE LANES SHALL BE SEALMASTER SAFE RIDE OR CITY APPROVED EQUIVALENT PER SECTION 64-6.01.
21. HYDRANT MARKERS MUST BE INSTALLED PER STD. 2920, DO NOT INSTALL IN BIKE LANES.
22. CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING UTILITY COVERS IN FIELD.
23. PROTECT UTILITY COVERS IN PLACE. ENSURE EXCESSIVE LIP BETWEEN COVER AND SLURRY DOES NOT FORM. THERMOPLASTIC STRIPING PLACED ON CONCRETE REQUIRES A PRIMER COAT PRIOR TO APPLICATION.

PROJECT SOILS REPORT

EARTH SYSTEMS PACIFIC
PREPARED BY: 4378 OLD SANTA FE ROAD
SAN LUIS OBISPO, CA 93401
DATE: November 12, 2021
UPDATED: N/A
REPORT NAME: ANHOLM NEIGHBORHOOD GREENWAY
SAN LUIS OBISPO, CALIFORNIA
PREPARED BY: Robert Down, PE
LICENSE: PE 70206

RAW EARTHWORK QUANTITIES (BIKE PATH)

AREA OF DISTURBANCE: 26,000 SQUARE FEET
MAXIMUM CUT HEIGHT: 4.0 FEET
MAXIMUM FILL HEIGHT: 1.0 FEET
RAW CUT: 1,150 CUBIC YARDS
RAW FILL: 920 CUBIC YARDS
ADJUSTED FILL: 1,150 CUBIC YARDS
(ASSUMED 25% SHRINKAGE)
NET QUANTITY: 0 CUBIC YARDS

THE APPROXIMATE RAW EARTHWORK QUANTITIES SHOWN HEREON REPRESENT THE ESTIMATED VOLUMETRIC DIFFERENCE CALCULATED BETWEEN THE PROPOSED SURGRADE AND EXISTING GRADE SURFACE, AND ARE SUBJECT TO CHANGE. THESE ESTIMATES DO NOT INCLUDE CONSIDERATIONS FOR LOSSES OR SWELLING DUE TO: SOIL AMBROSING, STABILIZATION, CONSTRUCTION TECHNIQUE, FOOTING & TRENCHING SPOILS, ETC. THESE CONSIDERATIONS, IN ADDITION TO ACTUAL FIELD CONDITIONS AND THE FINAL RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER, MAY SIGNIFICANTLY EFFECT THE FINAL IMPORT/EXPORT QUANTITIES. APPROXIMATE QUANTITIES SHOWN ON THESE PLANS ARE FOR PERMITTING PURPOSES ONLY. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CALCULATE ACTUAL QUANTITIES FOR THE PURPOSE OF CONSTRUCTION AND COST ESTIMATE. CONTRACTOR IS ALSO RESPONSIBLE FOR ADJUSTMENTS TO SLOPE HEDGE POINTS IN ORDER TO PROVIDE GRADED PAD AREA ADJACENT TO PATHS, WALKWAYS, AND ROADS FOR UTILITY BOXES, TRANSFORMERS, AND ABOVE GROUND UTILITY INFRASTRUCTURE.

APPROXIMATE RAW EARTHWORK QUANTITIES SHOWN ABOVE FOR BIKE PATH AREA BETWEEN FOOTHILL BLVD AND RAMONA DRIVE ONLY. APPROXIMATE RAW EARTHWORK QUANTITIES FOR REMAINING PROJECT AREAS ARE NOT PROVIDED. CONTRACTOR IS RESPONSIBLE FOR ANYTALL MATERIALS QUANTITIES, EARTHWORK QUANTITIES ASSOCIATED WITH WORK SHOWN HEREIN. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CALCULATE ACTUAL QUANTITIES FOR THE PURPOSE OF BIDDING. COST ESTIMATES AND CONSTRUCTION.

STORMWATER COMPLIANCE


NOTES:

THE PROJECT CONSISTS OF:

- ROAD AND PAVING SURFACE REPAIR
- SIDEWALK AND BIKE PATH
- CURB AND GUTTER IMPROVEMENT OR REPLACEMENT
- SEAL AND PAINTWORK
- CURB RAMP IMPROVEMENTS

THE PROJECT IS SUBSEQUENTLY EXEMPT FROM CENTRAL COAST POST-CONSTRUCTION STORMWATER REQUIREMENTS PER RESOLUTION R3-2013-0032. REFER TO PROJECT STORMWATER CONTROL PLAN APPLICATION FOR FURTHER DETAILS.

LEGEND:



TREE PROTECTION

1. PROTECT TREE BRANCHES, TRUNK, ROOTS AND FOLIAGE THROUGH PROPER TRIMMING AND CONSTRUCTION TECHNIQUES WHENEVER POSSIBLE. CONTRACTOR TO HIRE CERTIFIED ARBORIST FOR TREE TRIMMING TO ALLOW NECESSARY EQUIPMENT CLEARANCE AT NO ADDITIONAL COST TO THE CITY.
2. WHERE TREES CANNOT BE TRIMMED TO AVOID CONFLICT WITH CONSTRUCTION EQUIPMENT, THE FOLLOWING TECHNIQUES MAY BE UTILIZED TO MINIMIZE DAMAGE DURING CONSTRUCTION ACTIVITIES:
- a. USE EQUIPMENT THAT IS SHORTER IN HEIGHT OR WIDTH TO AVOID CONTACT WITH TREES
 - b. BACK EQUIPMENT UNDER LIMBS AND FOLIAGE TO MINIMIZE CONTACT WITH CONSTRUCTION EQUIPMENT
 - c. EMPLOY HAND TECHNIQUES TO AVOID USING EQUIPMENT UNDER VULNERABLE TREES
 - d. UNDER COORDINATION WITH THE CITY ARBORIST, PUSH INTERFERING TREE LIMBS TEMPORARILY OUT OF THE WAY.

LDS BIKE PATH NOTES

PER CITY OF SAN LUIS OBISPO GRANT DEED AND ROW AGREEMENT:

1. DEED SECTION 2 - RESTORATION OF GRANTOR PROPERTY: CONTRACTOR TO RESTORE AREAS IMPACTED BY CONSTRUCTION WITHIN THE TEMPORARY EASEMENT AREA LOCATED ON THE CHURCH OF JESUS CHRIST OF LATTER-DAY SAINTS ("GRANTOR") PROPERTY TO PRE-CONSTRUCTION CONDITION UPON COMPLETION OF CONSTRUCTION ACTIVITIES. THIS INCLUDES, BUT IS NOT LIMITED TO REMOVAL OF ALL EQUIPMENT AND MATERIALS; REPAIR OF ANY DAMAGE; AND REPLACEMENT OF TOPSOIL, VEGETATION, MULCH, ETC.
2. DEED SECTION 5.3 - USE OF EASEMENT AREA: CONTRACTOR SHALL NOT CARRY OUT ANY ACTIVITIES THAT CREATE NUISANCES OR POSE RISKS TO THE GRANTOR, INCLUDING BUT NOT LIMITED TO NOISES, ODORS, LIGHT, DUST, SMOKE, GASES, LIGHT, VIBRATION, RISK OF FIRE, EXPLOSION, OR HAZARDOUS MATERIALS.
3. ROW AGREEMENT - SECTION E: CONTRACTOR TO REINSTALL THE 6' HIGH METAL SECURITY FENCE, OR A COMPARABLE REPLACEMENT FENCE, ALONG FOOTHILL BOULEVARD AND FOR THE LENGTH OF THE PROPERTY LINE BETWEEN THE GRANTOR'S PROPERTY AND THE NEW EASEMENT AREA.
4. ROW AGREEMENT - SECTION E AS PART OF THE CONSTRUCTION PROJECT, THE CONTRACTOR PLANT EIGHT TREES WITHIN THE TEMPORARY CONSTRUCTION EASEMENT LOCATED ON THE GRANTOR'S PROPERTY.
5. CONTRACTOR TO COMPLY WITH THE FULL REQUIREMENTS DESCRIBED IN THE DEED AND RIGHT OF WAY AGREEMENT, WHICH ARE PROVIDED AS AN ATTACHMENT TO THE BID DOCUMENTS.

AC MILL AND FILL NOTES

1. PRIOR TO CONSTRUCTION, CONTRACTOR TO FIELD VERIFY DIMENSIONS WITH ENGINEER PRIOR TO SAWCUTTING AND DIG.
2. FIELD VERIFY WITH ENGINEER PRIOR TO REMOVAL OF BASE FAILURES. DIGOUTS OF BASE FAILURES SHALL BE REMOVED AND REPLACED PRIOR TO FIRST LIFT. DEPTH OF BASE DIGOUT TO BE DETERMINED BY GEOTECHNICAL ENGINEER.
3. ASSUMED CLASS II AGGREGATE BASE SUBGRADE ASSUMED TO BE SUFFICIENT AND TO BE PROTECTED IN PLACE. PRIOR TO CONSTRUCTION, ANY CHANGE IN DEPTH OF HMA OR CLASS II AGGREGATE BASE SUBGRADE MATERIAL TO BE COORDINATED WITH CITY AND GEOTECHNICAL ENGINEER.
4. PLACE 10" U.O.N. MIN HOT MIX ASPHALT (HMA) TYPE "A" IN LIFTS PER STATE STANDARD SPECIFICATIONS. THE INITIAL LIFT MUST BE 3-INCHES THICK (1/2" MAX AGGREGATE) AND FINAL LIFT BE 3-INCHES THICK (1/2" MAX AGGREGATE).
5. MILLING AND FILLING WITH THE INITIAL LIFT OF 3-INCHES MUST BE COMPLETED ON THE SAME WORK SHIFT. THE INITIAL LIFT OF 3-INCHES MUST BE COMPLETED FOR THE ENTIRE LENGTH AND WIDTH OF THE DESIGNATED AREA BEFORE THE FINAL LIFT CAN BE COMPLETED.
6. CONTRACTOR TO PAVE UP TO GUTTER LIP OR EDGE OF EXISTING PAVEMENT SAWCUT LINE.
7. PAVEMENT CROSS SLOPES SHALL MATCH EXISTING EXCEPT THAT CROSS SLOPES SHALL BE LIMITED TO 1.5% MINIMUM AND 3.0% MAXIMUM, UNLESS OTHERWISE APPROVED BY THE CITY AND/OR ENGINEER.
8. HMA AGGREGATE SIZE MUST COMPLY WITH CITY SPECIFICATIONS SECTION 39-3.01.

ABBREVIATIONS

AB	AGGREGATE BASE	WTS	HOT TO SCALE
AC	ASPHALT CONCRETE	FL	PROPERTY LINE
AP	ANGLE POINT	PCL	PARCELS
ARV	AIR RELEASE VALVE	PCC	PORTLAND CEMENT CONCRETE
BCR	BEHOLD CURVE	PCU	POINT OF CURVE/POINT OF CONNECTION
BW	BACK OF WALK	POT	POINT OF TANGENT
CB	CATCH BASIN	PRC	POINT OF REVERSE CURVE
CL/CUL	CENTERLINE/CLASS	ROW	RIGHT OF WAY
CMP	CORRUGATED METAL PIPE	RET WALL	RETAINING WALL
CONC	CONCRETE	RP	REDUCED PRESSURE
DBH	DIAMETER AT BREAST HEIGHT (OF A TREE)	RW	RECYCLED WATER
D	DRAIN INLET	SD	STORM DRAIN
DIP	DUCTILE IRON PIPE	SFM	SEWER FORCE MAIN
EG	EXISTING GRADE	SL	STREET LIGHT/OBSCURE LATERAL
EX	EXISTING	SS	SANITARY SEWER
ELEV	ELEVATION	STA	STATION
FDC	FIRE DEPARTMENT CONNECTION	STD.	STANDARD
FG	FINISHED GRADE	TSD	TO BE DETERMINED
FL	FLOWLINE	TBM	TEMPORARY BENCHMARK
FS	FINISHED SURFACE	TC	TOP OF CURB
FP	FINISHED PAD	TF	TOP OF FOOTING
FW	FINISHED WALK	TP	TOP OF PAVEMENT
HP	HIGH POINT	TG	TOP OF GRADE
HP	HIGH POINT SEE	TFP	TYPICAL
JT	JOINT TRENCH	TW	TOP OF WALL
LP	LOW POINT	UCHN	UNLESS OTHERWISE NOTED
EL	ELEVATION	W	WATER
MIN.	MINIMUM	WSE	WATER SURFACE ELEVATION



CERRO SAN LUIS GREENWAY

GENERAL NOTES

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036


PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-1.2

CIVIL SHEET INDEX LIST

SHEET NUMBER	SHEET TITLE
C-1.1	TITLE SHEET
C-1.2	GENERAL NOTES
C-1.3	KEYMAP
C-2.1	EXISTING CONDITIONS BIKE PATH (10+00 - 13+50)
C-2.2	EXISTING CONDITIONS CHORRO (13+25 - 42+25)
C-3.1	FERRINI
C-3.2	FERRINI
C-3.3	BIKE PATH (10+00 - 13+50)
C-3.4	BIKE PATH (13+50 - 15+25)
C-3.5	BIKE PATH RETAINING WALL
C-3.6	RAMONA (10+00 - 17+85)
C-3.7	BROAD (10+00 - 18+75)
C-3.8	BROAD (18+75 - 27+50)
C-3.9	MISSION (11+00 - 18+25)
C-3.10	CHORRO (10+00 - 17+50)
C-3.11	CHORRO (17+50 - 26+50)
C-3.12	LINCOLN (10+00 - 9+00)
C-3.13	CHORRO (26+50 - 29+50)
C-3.14	CHORRO (29+50 - 38+00)
C-3.15	CHORRO (18+00 - 41+00)
C-3.16	CHORRO (41+00 - 49+00)
C-4.1	FELTON CURB RETURNS
C-4.2	FELTON CURB RETURNS
C-4.3	CERRO ROMALUCCO CURB RETURNS
C-4.4	CERRO ROMALUCCO CURB RETURNS
C-4.5	RAMONA CURB RETURNS
C-4.6	RAMONA CURB RETURNS
C-4.7	RAMONA CURB RETURNS
C-4.8	MENECKE CURB RETURNS
C-4.9	MENECKE CURB RETURNS
C-4.10	MENECKE CURB RETURNS
C-4.11	MURRAY CURB RETURNS
C-4.12	MURRAY CURB RETURNS
C-4.13	MURRAY CURB RETURNS
C-4.14	MURRAY CURB RETURNS
C-4.15	BROAD CURB RETURNS
C-4.16	BROAD CURB RETURNS
C-4.17	ALMOND CURB RETURNS
C-4.18	MISSION CURB RETURNS
C-4.19	MISSION CURB RETURNS
C-4.20	MISSION CURB RETURNS
C-4.21	MISSION CURB RETURNS
C-4.22	MISSION CURB RETURNS
C-4.23	VENABLE CURB RETURNS
C-4.24	VENABLE CURB RETURNS
C-4.25	CENTER CURB RETURNS
C-4.26	CENTER CURB RETURNS
C-4.27	CENTER CURB RETURNS
C-4.28	CENTER CURB RETURNS
C-4.29	MOUNTAIN VIEW CURB RETURNS
C-4.30	MOUNTAIN VIEW CURB RETURNS
C-4.31	MOUNTAIN VIEW CURB RETURNS
C-4.32	MOUNTAIN VIEW CURB RETURNS
C-4.33	MOUNTAIN VIEW CURB RETURNS
C-4.34	LINCOLN CURB RETURNS
C-4.35	LINCOLN CURB RETURNS
C-4.36	LINCOLN CURB RETURNS
C-4.37	LINCOLN CURB RETURNS
C-4.38	WALNUT CURB RETURNS
C-4.39	WALNUT CURB RETURNS
C-4.40	WALNUT CURB RETURNS
C-4.41	WALNUT CURB RETURNS
C-4.42	PEACH CURB RETURNS
C-4.43	PEACH CURB RETURNS
C-4.44	PEACH CURB RETURNS
C-4.45	PEACH CURB RETURNS
C-4.46	MILL CURB RETURNS
C-4.47	MILL CURB RETURNS
C-4.48	MILL CURB RETURNS
C-4.49	MILL CURB RETURNS
C-5.1	DETAILS
C-5.2	DETAILS



KEYMAP

1" = 250' HORIZONTAL SCALE



CERRO SAN LUIS GREENWAY


KEYMAP

PROJECT TITLE



SHEET TITLE



DESIGNED BY	SKY
DRAWN BY	BLM
CHECKED BY	SKY
APPROVED BY	
SCALE	AS NOTED
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	C-1.3




CHORRO [33+25 - 38+00]



CHORRO [38+00 - 42+25]

1" = 20' HORIZONTAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOINT LOCATIONS AND REPORT ANY DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY FACTOR" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-3444 BEFORE ANY TRENCHING OR EXCAVATION WORK.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE. SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- PROTECT AND PRESERVE EXISTING SIGN AND POST IN PLACE.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◇ REMOVE AND RENEWAL EXISTING SIGN ON NEW PUNCH POST UNLESS EXISTING POST CAN BE SALVAGED PER CITY STD. 7315.
- ◇ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◇ PROJECT IN PLACE (S) STORM DRAIN (R). REPLACE (S) STORM DRAIN GRATE WITH (R) COMB COMB CALTRANS TYPE 18-18 OR 24-18, ACCORDING TO ITS REFERENCE TO CALTRANS STD. D778. DIMENSIONS PER PLAN. INSTALL FLEXTRIX STORMEXX CLEAN CATCH BASH HOLE TO TOP, OR APPROVED EQUAL.
- ◇ REMOVE AND RENEWAL SPEED HUMP (TYPE S) PER CITY STD. 7320 & 7321.
- ◇ REMOVE AND RENEWAL SPEED TABLE PER CITY STD. 7325.
- ◇ REMOVE EXISTING CONCRETE CURB.
- ◇ REMOVE EXISTING CONCRETE CURB AND GUTTER.
- ◇ REMOVE EXISTING TREE, INCLUDING STUMPS AND ROOTS.
- ◇ REMOVE ALL EXISTING VEGETATION WITHIN EXISTING 20' EASEMENT.
- ◇ REMOVE EXISTING DRIP IRRIGATION LINES, STUB AND CAP AT L25 PROPERTY.



CERRO SAN LUIS GREENWAY

EXISTING CONDITIONS CHORRO [33+25 - 42+25]

PROJECT TITLE

SHEET TITLE



DESIGNED BY:	SKY
DRAWN BY:	BLM
CHECKED BY:	SKY
APPROVED BY:	
SCALE:	AS NOTED
DATE:	JUNE 2, 2022
CITY SPECIFICATION NO.:	1000036
PLAN FILE NO. LOCATION:	1417-05-CU21
SHEET NO.:	C-2.2



STATE HWY 1 / N. SANTA ROSA

HIGHLAND

N. CHORO

FERRINI

FERRINI

1" = 20' HORIZONTAL SCALE



0 20 40 60 feet
1" = 20'

FERRINI

1" = 20' HORIZONTAL SCALE



0 20 40 60 feet
1" = 20'

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JUNCTION LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CIVASCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TRIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 21.10. WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4130.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROJECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH SCHOTCHDORF CALTRANS TYPE 18-BX OR 24-18, ACCORDING TO ITS REFER TO CALTRANS STD D778. DIMENSIONS PER PLAN. INSTALL FILTEREXX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-22(C)250. MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 2' BEYOND HANDSCAPE ISOLS. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (PM-A) TYPE "A" (1 1/2" MAX. AGGREGATE).
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

FERRINI


PROJECT TITLE

SHEET TITLE




DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO / LOCATION: 1417-05-CU21
SHEET NO:

C-3.1



FERRINI

1" = 20' HORIZONTAL SCALE



FERRINI


1" = 20' HORIZONTAL SCALE

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOINT LOCATIONS AND REPORT ANY ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 21.10. WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB PER CITY STD. 4030.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (P) STORM DRAIN INLET. REPLACE (R) STORM DRAIN GRATE WITH (R) CHOTECOMB CALTRANS TYPE 18-R OR 24-16, ACCORD TO ITS REFER TO CALTRANS STD D778. DIMENSIONS PER PLAN. INSTALL FILTEREXX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-22(C)220. MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 2" BEYOND HANDSCAPE EDGE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MAX. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1/2" MAX. AGGREGATE).
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

FERRINI

PROJECT TITLE

SHEET TITLE



DESIGNED BY

DRAWN BY:

CHECKED BY:

APPROVED BY:

AS NOTED

DATE:

JUNE 2, 2022

CITY SPECIFICATION NO.


1000036

PLAN FILE NO. LOCATION

1417-05-CU21

SHEET NO.


C-3.2




BIKE PATH [10+00 - 13+50]

1" = 20' HORIZONTAL SCALE


1" = 4' VERTICAL SCALE



SEC A-A: BIKE PATH



SEC B-B: BIKE PATH



NOTES:


1. PROTECT AND PRESERVE EXISTING WALL AND FOOTING. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL POHOLE AND FIELD VERIFY EXISTING DEPTH AND EXTENT OF EXISTING WALL FOOTING. CONTRACTOR SHALL IDENTIFY AND REPORT ANY POTENTIAL CONFLICTS WITH PROPOSED WALL FOOTING AND/OR PROPOSED FOOTING CONSTRUCTION AS SOON AS FEASIBLE. INFORMATION FOUND SHALL BE SHARED WITH CITY AND ENGINEER OF RECORD.

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CIVAS 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CA MUTCD) AND THE LATEST CALIFORNIA STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TRIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 21.10: WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB PER CITY STD. 4020.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440.
- ◆ SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH CONFORMING CAUTION TYPE (B) OR 24.15. ACCORDING TO ITS REFER TO CALTRANS STD D778 DIMENSIONS PER PLAN. INSTALL FILTERED STORMWATER CLEAN CATCH BASIN INLET TUBE, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-201(C)(2). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXISTING SLEEVES 18" BEYOND HARDSCAPE EDGE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (BMA) TYPE "A" (1/2" MAX AGGREGATE).
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.




CERRO SAN LUIS GREENWAY

BIKE PATH [10+00 - 13+50]

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY

BLM

CHECKED BY

SKY

APPROVED BY

AS NOTED

DATE:

JUNE 2, 2022

CITY SPECIFICATION NO.

1000036

PLAN FILE NO. LOCATION:

1417-05-CU21

SHEET NO.

C-3.3



CERRO SAN LUIS GREENWAY


BIKE PATH [13+50 - 15+32]

PROJECT TITLE

SHEET TITLE





DESIGNED BY	SKY
DRAWN BY	BLM
CHECKED BY	SKY
APPROVED BY	SKY
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	C-3.4



BIKE PATH [13+50 - 15+32]


1" = 20' HORIZONTAL SCALE
1" = 4' VERTICAL SCALE



PER CITY OF SAN LUIS OBISPO GRANT DEED AND ROW AGREEMENT:

- DEED SECTION 2 - RESTORATION OF GRANATOR PROPERTY: CONTRACTOR TO RESTORE AREAS IMPACTED BY CONSTRUCTION WITHIN THE TEMPORARY EASEMENT AREA LOCATED ON THE CHURCH OF JESUS CHRIST OF LATTER-DAY SAINTS (FORANOT) PROPERTY TO PRE-CONSTRUCTION CONDITION UPON COMPLETION OF CONSTRUCTION ACTIVITIES. THIS INCLUDES, BUT IS NOT LIMITED TO, REMOVAL OF ALL EQUIPMENT AND MATERIALS, REPAIR OF ANY DAMAGE, AND REPLACEMENT OF TOPSOIL, VEGETATION, MULCH, ETC.
- DEED SECTION 5.3 - USE OF EASEMENT AREA: CONTRACTOR SHALL NOT CARRY OUT ANY ACTIVITIES THAT CREATE NUISANCES OR POSSIBLE RISKS TO THE GRANATOR, INCLUDING BUT NOT LIMITED TO NOISE, ODORS, LIGHT, DUST, SHAKES, GASES, LIGHT VIBRATION, RISK OF FIRE, EXPLOSION, OR HAZARDOUS MATERIALS.
- ROW AGREEMENT - SECTION 6: CONTRACTOR TO REINSTALL THE 6" HIGH METAL SECURITY FENCE, OR A COMPARABLE REPLACEMENT FENCE, ALONG FOOTBALL BOULEVARD AND FOR THE REMAINDER OF THE PROPERTY LINE BETWEEN THE GRANATOR'S PROPERTY AND THE NEW EASEMENT AREA.
- ROW AGREEMENT - SECTION 8: AS PART OF THE CONSTRUCTION PROJECT, THE CONTRACTOR SHALL PLANT EIGHT TREES WITHIN THE TEMPORARY CONSTRUCTION EASEMENT LOCATED ON THE GRANATOR'S PROPERTY.
- CONTRACTOR TO COMPLY WITH THE FULL REQUIREMENTS DESCRIBED IN THE DEED AND RIGHT OF WAY AGREEMENT, WHICH ARE PROVIDED AS AN ATTACHMENT TO THE BID DOCUMENTS.


SEC C-C: BIKE PATH



NOTES

- PROTECT AND PRESERVE EXISTING WALL AND FOOTING. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL PINHOLE AND FIELD VERIFY EXISTING DEPTH AND EXTENTS OF EXISTING WALL FOOTING. CONTRACTOR SHALL IDENTIFY AND REPORT ANY POTENTIAL CONFLICTS WITH PROPOSED WALL FOOTING AND/OR PROPOSED FOOTING CONSTRUCTION AS SOON AS FEASIBLE. INFORMATION FOUND SHALL BE SHARED WITH CITY AND ENGINEER OF RECORD.

SEC D-D: BIKE PATH



NOTES


- PROTECT AND PRESERVE EXISTING WALL AND FOOTING. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL PINHOLE AND FIELD VERIFY EXISTING DEPTH AND EXTENTS OF EXISTING WALL FOOTING. CONTRACTOR SHALL IDENTIFY AND REPORT ANY POTENTIAL CONFLICTS WITH PROPOSED WALL FOOTING AND/OR PROPOSED FOOTING CONSTRUCTION AS SOON AS FEASIBLE. INFORMATION FOUND SHALL BE SHARED WITH CITY AND ENGINEER OF RECORD.

NOTES

- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CLAUSE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1.800.642.2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCS) AND THE LATEST CALIFORNIA STANDARD PLANS AND SPECIFICATIONS.
- REMOVE AND REPLACE ALL STRIPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
- SALVAGE ALL TRIED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.



IMPROVEMENT KEY NOTES

- CONSTRUCT DRIVEWAY RAMP PER CITY STD. 21.10: WIDTH PER PLAN.
- CONSTRUCT 6" CURBS PER CITY STD. 4020.
- CONSTRUCT 6" CURBS AND 18" GUTTER PER CITY STD. 4020.
- CONSTRUCT SIDEWALK PER CITY STD. 4110.
- CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440.
- SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- INSTALL TYPE I SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH CONCRETE/COMB CALTRANS TYPE (B) OR 24" IS. ACCORDING TO HS. REFER TO CALTRANS STD 0778, DIMENSIONS PER PLAN. INSTALL FILTERX STORMEXX CLEAN CATCH BASIN INLET TRUS, OR APPROVED EQUAL.
- INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20.20.20. MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 12" BEYOND HARDSCAPE EDGE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MAX. PLACE HOT MIX ASPHALT (90A) TYPE "A" (1/2" MAX. AGGREGATE).
- REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



RETAINING WALL(W)

1" = 20' HORIZONTAL SCALE
1" = 4' VERTICAL SCALE



CERRO SAN LUIS GREENWAY

BIKE PATH RETAINING WALL

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO/LOCATION: 1417-05-CU21


SHEET NO:

C-3.5



MISSION [11+00 - 14+00]

1" = 20' HORIZONTAL SCALE



MISSION [14+00 - 18+25]

1" = 20' HORIZONTAL SCALE

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TYPED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 2110, WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB PER CITY STD. 4020.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (P) STORM DRAIN INLET. REPLACE (R) STORM DRAIN GRATE WITH SCHOTCHORP CALTRANS TYPE 18-R OR 24-18, ACCORDING TO ITS REFER TO CALTRANS STD D778, DIMENSIONS PER PLAN. INSTALL FILTEREXX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-2.01(C)(20). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SUBEVES 12" BEYOND HANDSCAPE EDGE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND RENEWALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1 1/2" MAX AGGREGATE).
- ◆ REMOVE AND RENEWALL SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

MISSION [11+00 - 18+25]


PROJECT TITLE

SHEET TITLE




DESIGNED BY:	SKY
DRAWN BY:	BLM
CHECKED BY:	SKY
APPROVED BY:	
SCALE:	AS NOTED
DATE:	JUNE 2, 2022
CITY SPECIFICATION NO:	1000036
PLAN FILE NO / LOCATION:	1417-05-CU21
SHEET NO:	

C-3.9



LINCOLN [6+05 - 9+00]

1" = 20' HORIZONTAL SCALE




NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CIVASCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 2110, WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB PER CITY STD. 4030.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4310.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (E) STORM DRAIN INLET. REPLACE (E) STORM DRAIN GRATE WITH SCHOTCHOMB CALTRANS TYPE 18-RS OR 24-18, ACCORDING TO FIT. REFER TO CALTRANS STD D778, DIMENSIONS PER PLAN. INSTALL FILTERXX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-2.01(C)(2)(D). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 12" BEYOND HANDSCAPE ISOLS. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1 1/2" MAX AGGREGATE).
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

LINCOLN [6+05 - 9+00]

PROJECT TITLE

SHEET TITLE



DESIGNED BY:

SKY

DRAWN BY:

BLM

CHECKED BY:

SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO. 1000036

PLAN FILE NO. LOCATION 1417-05-CU21


SHEET NO.

C-3.12



CHORRO [26+50 - 29+50]

1" = 20' HORIZONTAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 2110. WIDTH PER PLAN.
- ◆ CONSTRUCT 4" CURB PER CITY STD. 4020.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (P) STORM DRAIN INLET. REPLACE (R) STORM DRAIN GRATE WITH 18"X24"X2" CALTRANS TYPE 18-R OR 24-18, ACCORDING TO FIT. REFER TO CALTRANS STD D778. DIMENSIONS PER PLAN. INSTALL FILTERXXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-2.01(C20). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 12" BEYOND HANDSCAPE ISOLE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND RENEW SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. ORRD EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1 1/2" MAX AGGREGATE).
- ◆ REMOVE AND RENEW SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

CHORRO [26+50 - 29+50]

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO. LOCATION: 1417-05-CU21

SHEET NO:

C-3.13



CERRO SAN LUIS GREENWAY

CHORRO [29+50 - 38+00]

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY: SKY
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-3.14

NOTES



1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JUNCTION LOCATIONS AND REPORT ANY ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHASSIS 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
5. REMOVE AND REPLACE ALL STRIPPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
6. SALVAGE ALL TIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- ◆ CONSTRUCT DRIVEWAY RAMP PER CITY STD. 21.10, WIDTH PER PLAN.
- ◆ CONSTRUCT 6" CURB PER CITY STD. 4030.
- ◆ CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- ◆ CONSTRUCT SIDEWALK PER CITY STD. 4110.
- ◆ CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- ◆ CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- ◆ INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH SCHOTCHORP CALTRANS TYPE 18-BX OR 24-18, ACCORDING TO ITS REFER TO CALTRANS STD D778, DIMENSIONS PER PLAN. INSTALL FILTEREX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- ◆ INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-2.07(C20). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 12" BEYOND HANDSCAPE EDGE. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MAX. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1 1/2" MAX AGGREGATE).
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



CHORRO [29+50 - 33+25]


1" = 20' HORIZONTAL SCALE



CHORRO [33+25 - 38+00]



1" = 20' HORIZONTAL SCALE





CHORRO [38+00 - 41+50]

1" = 20' HORIZONTAL SCALE
1" = 4' VERTICAL SCALE



NOTE:
THERE ARE EXISTING SHALLOW UTILITIES WITHIN PROPOSED WORK AREA. CONTRACTOR SHALL PROTECT AND PRESERVE EXISTING UTILITIES IN PLACE AND COORDINATE WITH GEOTECHNICAL ENGINEER.

NOTES

- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL SIGNAGE AND STRIPING SHALL CONFORM TO THE LATEST CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CMUTCD) AND THE LATEST CALTRANS STANDARD PLANS AND SPECIFICATIONS.
- REMOVE AND REPLACE ALL STRIPING IN PLACE, UNLESS OTHERWISE NOTED U.O.N.
- SALVAGE ALL TRIMED PARKING SIGNS AND RETURN THEM TO CITY CORPORATION YARD.

IMPROVEMENT KEY NOTES

- CONSTRUCT DRIVEWAY RAMP PER CITY STD. 2110, WIDTH PER PLAN.
- CONSTRUCT 4" CURB PER CITY STD. 4030.
- CONSTRUCT 6" CURB AND 18" GUTTER PER CITY STD. 4030.
- CONSTRUCT SIDEWALK PER CITY STD. 4110.
- CONSTRUCT CROSS GUTTER PER CITY STD. 4310.
- CONSTRUCT CURB RAMP AND DETECTABLE WARNING SURFACE PER CITY STD. 4440. SEE CURB RETURN SHEETS FOR GRADING AND DIMENSIONS.
- INSTALL TYPE II SLURRY SEAL PER CITY SPECIFICATIONS, SECTION 37.
- PROTECT IN PLACE (E) STORM DRAIN INLET. REPLACE (E) STORM DRAIN GRATE WITH CHOTECOMB CAULDRONS TYPE 18-8R OR 24-18, ACCORDING TO FIT. REFER TO CALTRANS STD D778, DIMENSIONS PER PLAN. INSTALL FILTEREXX STORMEXX CLEAN CATCH BASH INLET FILTER, OR APPROVED EQUAL.
- INSTALL 2" PVC SCHEDULE 40 IRRIGATION SLEEVE, U.O.N. PER CITY SPEC SECTION 20-201(C)(2). MINIMUM DEPTH OF 18 INCHES BELOW FINISH GRADE. EXTEND SLEEVES 12" BEYOND HANDSCAPE ISOLS. SEE LANDSCAPE IRRIGATION PLANS FOR DETAILS.
- REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321. GRIND EXISTING ASPHALT, 1" MIN. PLACE HOT MIX ASPHALT (HMA) TYPE "A" (1 1/2" MAX. AGGREGATE).
- REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.



CERRO SAN LUIS GREENWAY

CHORRO [38+00 - 41+50]

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY

BLM

CHECKED BY

SKY

APPROVED BY

AS NOTED

DATE

JUNE 2, 2022

CITY SPECIFICATION NO.


1000036

PLAN FILE NO. LOCATION

1417-05-CU21

SHEET NO.

C-3.15




FELTON CURB RETURNS

CONNECTED:




C-4.1



FERRINI | FELTON (NW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING HERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK GUARANTEES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-15, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

FELTON CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.2



1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING PROJECT. THE CONTRACTOR SHALL VERIFY THE EXISTING SITE CONDITIONS VERY RY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOINT LOCATIONS AND REPORT ANY DISCREPANCIES TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR RESPECTIVE PRIOR TO CONSTRUCTION.

2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CLAUSE 38.02 AS DEFINED IN THE 2012 EDITION OF THE DEPARTMENT OF TRANSPORTATION'S "MANUAL ON PRACTICES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT UTA NORTH AT 1-800-442-2446 BEFORE ANY TRENCHING OR EXCAVATION WORK.

4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, THE PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING ENGINEER. THE CONTRACTOR SHALL CONSULT THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THE CONTRACT DOCUMENTS.

6. DO NOT PERFORM LANDSCAPE PLANTING FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.

7. NO CUTTING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.

8. REFER TO "GEOTECHNICAL SPECIAL INSPECTION" ON THE GENERAL NOTES SHEET FOR CRITICAL ROOT ZONE AND CRITICAL ROOT ZONE PROTECTION DETAILS.

9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROPRIATE CUT AND FILL DATA.

10. ALL CONSTRUCTION SHALL MAINTAIN AND VALUES TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.

11. LANDSCAPE APPLICABLE TRENCHING AND INSTALLATION SHALL BE COMPLETED TO THE BOTTOM OF THE TRENCHING.

- 1 PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- 2 PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- 3 PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- 4 PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- 5 NOT USED.
- 6 PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SEWERAGE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PRIORIT # IN PLACE (C) STORM DRAIN INLET, REPLACE (E) STORM DRAIN GRATE WITH 15" X 15" ALUMINUM TYPE 15-06 OR 24-10, ACCORDING TO TYPE. REFER TO CALTRANS SD D776, COMBOSONS PER PLAN, RETAIL, BUSTLE, FISHBONE, CATCH CATCH BASIN AND CATCH BASIN APPROVED.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL STRENGTH SCALE PER CITY STD. 7323.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCURE CURB AND GUTTER.

CERRO ROMAULDO CURB RETURNS

SWEET TO GO:



C-4.3

C-4.5



CERRO SAN LUIS GREENWAY
RAMONA CURB RETURNS



DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-4.7

NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.


SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (S) STORM DRAIN INLET. REPLACE (S) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 127B, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



BROAD | RAMONA (SW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE





CERRO SAN LUIS GREENWAY

MEINECKE CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-4.10

NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING HERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO GEOTECHNICAL SPECIAL INSPECTIONS ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "BATHROOM QUARTERS" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.


PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APERTURES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD 107B, COMBING PER PLAN. INSTALL FUTURES STORMSE CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.






MURRAY - SEE NEXT SHEET

BROAD | MURRAY (NE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 307B, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MURRAY CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO. LOCATION: 1417-05-CU21

SHEET NO:


C-4.11



BROAD

BROAD | MURRAY (E)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
- REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
- NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
- REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
- REFER TO "WATERWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
- ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
- LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S. MODIFIED TO FIT. REFER TO CALTRANS STD 307B, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- REMOVE EXISTING CONCRETE CURBS.
- REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MURRAY CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY

BLM

CHECKED BY

SKY

APPROVED BY

SCALE:

AS NOTED

DATE:

JUNE 2, 2022

CITY SPECIFICATION NO.


1000036

PLAN FILE NO. LOCATION:

1417-05-CU21



SHEET NO.

C-4.12



BROAD | MURRAY (SE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CIVASCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE; ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 107B, COMBING PER PLAN. INSTALL FUTURE STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MURRAY CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036


PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.13



BROAD | MISSION (NE)
1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
- REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
- NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
- REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
- REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
- ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
- LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 127B, COMBING PER PLAN. INSTALL FILTERBOX STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

BROAD CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO. LOCATION: 1417-05-CU21


SHEET NO:

C-4.15



MISSION | ALMOND (SE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
- REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
- NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
- REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
- REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
- ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
- LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- PROTECT IN PLACE (E) STORM DRAIN INLET. REPLACE (E) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-105, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- REMOVE EXISTING CONCRETE CURB.
- REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

ALMOND CURB RETURN

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036


PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.17



MISSION BULBOUT
1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY "NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-3444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "TERRAIN QUANTITIES" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "TERRAIN QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD D778, COMBING PER PLAN. INSTALL FUTURE STORMSINK CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MISSION CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY

BLM

CHECKED BY

SKY

APPROVED BY

SCALE

AS NOTED

DATE

JUNE 2, 2022

CITY SPECIFICATION NO.


1000036

PLAN FILE NO. LOCATION

1417-05-CU21


SHEET NO.

C-4.18



CHORRO | MISSION (NE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO GEOTECHNICAL SPECIAL INSPECTIONS ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "BATHROOM QUARTERS" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE; ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBINGS PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MISSION CURB RETURNS

PROJECT TITLE

SHEET TITLE



DRAWN BY: SKY

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036




PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.20

CHORRO | MISSION (SE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD 107B, COMBINED PER PLAN. INSTALL FILTERED STORMWATER CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MISSION CURB RETURNS


PROJECT TITLE

SHEET TITLE



DRAWN BY:	SKY
CHECKED BY:	BLM
APPROVED BY:	SKY
SCALE:	AS NOTED
DATE:	JUNE 2, 2022
CITY SPECIFICATION NO:	1000036
PLAN FILE NO:	1417-05-CU21
SHEET NO:	

C-4.21




CHORRO | MISSION (SW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



MISSION



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING HERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
8. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
9. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
10. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBINED PER PLAN. INSTALL FUTURE STORMSINK CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MISSION CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY

BLM

CHECKED BY

SKY

APPROVED BY

AS NOTED

DATE:

JUNE 2, 2022

CITY SPECIFICATION NO.

1000036

PLAN FILE NO. LOCATION:

1417-05-CU21

SHEET NO.

C-4.22



CERRO SAN LUIS GREENWAY

VENABLE CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY	SKY
DRAWN BY	BLM
CHECKED BY	SKY
APPROVED BY	
SCALE	AS NOTED
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	

C-4.24

NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS, AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHASSIS 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK GUARANTEES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.


SITE PREPARATION KEY NOTES


- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 027B, COMBING PER PLAN. INSTALL FUTURES STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CHORRO | VENABLE (SE)



1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE





CHORRO | CENTER (NW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "TC" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-15, MODIFIED TO FIT. REFER TO CALTRANS STD D278, COMBING PER PLAN. INSTALL FUTURES STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

CENTER CURB RETURNS


PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-4.25



CHORRO | MOUNTAIN VIEW (SE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHASICE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT USA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◇ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◇ REFER TO SIGNAGE AND STRIPING PLANS FOR SIGN DISPOSITION.
- ◇ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◇ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10S. MODIFIED TO FIT. REFER TO CALTRANS STD D778, COMBINGS PER PLAN. INSTALL FUTURES STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◇ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◇ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◇ REMOVE EXISTING CONCRETE CURBS.
- ◇ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

MOUNTAIN VIEW CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21


SHEET NO:

C-4.32



CHORRO | LINCOLN (NW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO GEOTECHNICAL SPECIAL INSPECTIONS ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "BATHROOM QUARTERS" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMSINK CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

LINCOLN CURB RETURNS


PROJECT TITLE

SHEET TITLE




DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-4.34



CHORRO | LINCOLN (SE)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO GRADING NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

LINCOLN CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21


SHEET NO:

C-4.36



CHORRO | LINCOLN (SW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO "UTILITY NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHES.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK GUARANTEES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

LINCOLN CURB RETURNS

PROJECT TITLE

SHEET TITLE



DRAWN BY: SKY

CHECKED BY: BLM

APPROVED BY: SKY

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.37



CERRO SAN LUIS GREENWAY

WALNUT CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY

SKY

DRAWN BY:

BLM

CHECKED BY:

SKY

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.39



CHORRO | WALNUT (S)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES


1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCIES FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CLAUSE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
- REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK GUARANTEES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (S) STORM DRAIN INLET. REPLACE (S) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-1DS, MODIFIED TO FIT. REFER TO CALTRANS STD 327B, COMBING PER PLAN. INSTALL FUTURE STORMSINK CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

WALNUT CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036


PLAN FILE NO. LOCATION: 1417-05-CU21

SHEET NO.

C-4.40

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.




CERRO SAN LUIS GREENWAY

WALNUT CURB RETURNS

PROJECT TITLE



DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY: SKY
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO: C-4.41



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
4. ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 107B, COMBING PER PLAN. INSTALL FUTURE STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

PEACH CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY:	SKY
DRAWN BY:	BLM
CHECKED BY:	SKY
APPROVED BY:	SKY
SCALE:	AS NOTED
DATE:	JUNE 2, 2022
CITY SPECIFICATION NO:	1000036
PLAN FILE NO/LOCATION:	1417-05-CU21
SHEET NO:	

C-4.42



CERRO SAN LUIS GREENWAY

PEACH CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY	SKY
DRAWN BY	BLM
CHECKED BY	SKY
APPROVED BY	
SCALE	AS NOTED
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	

C-4.43

NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "EARTHWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES



- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.


SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-BB OR 24-10S, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBING PER PLAN. INSTALL FUTURE STORMS CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.

CHORRO | PEACH (SE)


1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE





CHORRO | PEACH (SW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES

1. THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
2. SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
3. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-2444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
5. THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
6. REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
7. NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
8. REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
9. REFER TO "WATERWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
10. ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
11. LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SIZE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPURTENANCES IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-15, MODIFIED TO FIT. REFER TO CALTRANS STD 207B, COMBINATION PER PLAN. INSTALL FUTURE STORMWATER CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7325.
- ◆ REMOVE EXISTING CONCRETE CURBS.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

PEACH CURB RETURNS


PROJECT TITLE

SHEET TITLE




DESIGNED BY: SKY
DRAWN BY: BLM
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:

C-4.44



CHORRO | PEACH (NW)

1" = 5' HORIZONTAL SCALE
1" = 1' VERTICAL SCALE



NOTES


- THE EXISTING SITE CONDITIONS SHOWN HEREIN HAVE BEEN COMPILED BASED ON TOPOGRAPHIC FIELD SURVEYS AND AS-BUILT DRAWINGS OF THE EXISTING IMPROVEMENTS. IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO VERIFY FIELD CONDITIONS, ESPECIALLY AT CRITICAL JOIN LOCATIONS AND REPORT ANY/ALL DISCREPANCIES IMMEDIATELY TO THE ENGINEER OF RECORD AND THE GOVERNING AGENCY FOR THEIR REVIEW PRIOR TO CONSTRUCTION.
- SUBSURFACE UTILITY DATA IS DEPICTED TO LEVEL "C" OF CHANCE 38-02 AS DEFINED IN THE GUIDELINE FOR DEPICTION OF EXISTING SUBSURFACE UTILITY DATA. REFER TO UTILITY NOTES ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- IT IS THE RESPONSIBILITY OF THE PROJECT CONTRACTOR TO CONTACT SEA NORTH AT 1-800-642-3444 BEFORE ANY TRENCHING OR EXCAVATION WORK.
- ALL GRADING SHALL BE IN CONFORMANCE WITH APPLICABLE LOCAL GRADING ORDINANCES, THE STANDARDS AND REQUIREMENTS PERTAINING THERETO, THIS PLAN, AND THE RECOMMENDATIONS AND REQUIREMENTS OF THE SUPERVISING GEOTECHNICAL ENGINEER. REFER TO "GRADING NOTES" ON THE GENERAL NOTES SHEET FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- THE GEOTECHNICAL ENGINEERING REPORT, IN ITS ENTIRETY, SHALL BE CONSIDERED A PART OF THESE PLANS.
- REFER TO LANDSCAPE PLANS FOR SIGNAGE, SITE FURNISHINGS, AND PAVEMENT FINISHING.
- NO GRADING, TRENCHING, OR GROUND DISTURBING ACTIVITIES SHALL BE CONDUCTED WITHIN THE CRITICAL ROOT ZONE OF TREES TO REMAIN.
- REFER TO "GEOTECHNICAL SPECIAL INSPECTIONS" ON THE GENERAL NOTES SHEET FOR REQUIRED CONTINUOUS AND PERIODIC INSPECTION AND TESTING OF SOILS.
- REFER TO "WATERWORK QUANTITIES" ON THE GENERAL NOTES SHEET FOR APPROXIMATE CUT AND FILL DATA.
- ADJUST EXISTING UTILITY MANHOLES AND VAULTS TO GRADE IN CONFORMANCE WITH APPLICABLE LOCAL STANDARDS AND SPECIFICATIONS.
- LANDSCAPE IRRIGATION TRENCHING AND INSTALLATION SHALL BE COMPLETED PRIOR TO BIO-RETENTION SOIL MEDIA INSTALLATION AND PLANTING.

PROTECTION KEY NOTES

- PROTECT AND PRESERVE EXISTING TREE IN PLACE; SEE PER PLAN.
- PROTECT AND PRESERVE EXISTING UTILITY VAULTS, MANHOLES, AND OTHER SURFACE APPOINTMENTS IN PLACE. ADJUST TO FINISHED GRADE WHERE NECESSARY.
- PROTECT AND PRESERVE EXISTING FIRE HYDRANT IN PLACE.
- PROTECT AND PRESERVE EXISTING UTILITY POLES AND STREET LIGHTS IN PLACE.
- NOT USED.
- PROTECT AND PRESERVE EXISTING SIDEWALK/DRIVEWAY IN PLACE.

SITE PREPARATION KEY NOTES

- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB, GUTTER, AND SIDEWALK.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING CURB DRAIN INFRASTRUCTURE.
- ◆ REMOVE AND PROPERLY DISPOSE OF EXISTING DRIVEWAY.
- ◆ REFER TO SIGNAGE AND STRIPPING PLANS FOR SIGN DISPOSITION.
- ◆ SAWCUT AND REMOVE EXISTING ASPHALT PAVEMENT.
- ◆ PROTECT IN PLACE (B) STORM DRAIN INLET. REPLACE (B) STORM DRAIN GRATE WITH HONEYCOMB CALTRANS TYPE 18-B OR 24-10, MODIFIED TO FIT. REFER TO CALTRANS STD D278, COMBING PER PLAN. INSTALL FUTURE STORMSEAL CLEAN CATCH BASIN INLET FILTER, OR APPROVED EQUAL.
- ◆ REMOVE AND REINSTALL SPEED HUMP (TYPE 2) PER CITY STD. 7320 & 7321.
- ◆ REMOVE AND REINSTALL SPEED TABLE PER CITY STD. 7320.
- ◆ REMOVE EXISTING CONCRETE CURB.
- ◆ REMOVE EXISTING CONCRETE CURB AND GUTTER.



CERRO SAN LUIS GREENWAY

PEACH CURB RETURNS

PROJECT TITLE

SHEET TITLE



DESIGNED BY: SKY

DRAWN BY: BLM

CHECKED BY: SKY

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022


CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

C-4.45





24"x36" SIGN VARIES PER STREET.
BACKGROUND:GREEN, LEGEND:WHITE
CITY WILL PROVIDE GRAPHIC FILES


A GREENWAY SIGN
NOT TO SCALE



DOUBLE ARROW PLAQUE



LEFT ARROW PLAQUE




RIGHT ARROW PLAQUE

BACKGROUND:GREEN
LEGEND & BORDER:WHITE




AREA = 45.5 SQFT
WHITE MARKINGS
NOTE: (1) GREEN WAY SYMBOL FURNISHED BY CITY


B GREEN WAY SYMBOL
NOT TO SCALE




C GREENBACK SHARROW
NOT TO SCALE



D LEFT-TURN BIKE BOX
NOT TO SCALE



K GREENBACK CHEVRON
NOT TO SCALE




E BIKE/PEL DIRECTIONAL SYMBOLS
NOT TO SCALE


NOTE: MARKINGS SHALL BE MELT-DOWN
THERMOPLASTIC SHEETS (ENNIS FLINT OR
CITY-APPROVED EQUIVALENT PRODUCT).




F BIKE BUFFER
NOT TO SCALE



G ZICLA ZEBRA
NOT TO SCALE




H BIKE BUFFER AT DRIVEWAY
NOT TO SCALE



LAYOUT


3' WIDE CONCRETE MEDIAN




LAYOUT

1.25' WIDE CONCRETE MEDIAN

J CONCRETE MEDIAN DETAIL (MODIFIED CITY STD. 4940)
NOT TO SCALE



SECTION A-A



SECTION B-B

INSTALLATION NOTES:

- 1 RECTANGULAR CAST IRON PIPE (ALHAMBRA A-470, SOUTH BAY FOUNDRY A9000 OR APPROVED EQUAL) TO BE INSTALLED 10' MINIMUM FROM NOSE END OF CURBED MEDIAN AND AT 20' MINIMUM SPACING
- 2 TYPE A3 CURB PER CALTRANS 2015 RSP A87A, DOWELLED IN TO EXISTING PAVEMENT SURFACE.
- 3 CLASS 3 CONCRETE WITH EXPANSION JOINTS AND WEAKENED PLANE JOINTS PER CITY STD 4110.
- 4 #4 REBAR AT 4'-0" OC, 12" MIN. LENGTH, DRIVEN IN PLACE
- 5 #4 LONGITUDINAL BAR
- 6 MEDIAN WORK SHALL CONFORM TO THE PROVISIONS IN SECTION 73, OF THE STANDARD SPECIFICATIONS.



CERRO SAN LUIS GREENWAY

DETAILS

PROJECT TITLE

SHEET TITLE



DESIGNED BY

DRAWN BY

CHECKED BY

APPROVED BY

SCALE

DATE

CITY SPECIFICATION NO.

PLAN FILE NO. LOCATION

SHEET NO.

C-5.1



CERRO SAN LUIS GREENWAY

DETAILS

PROJECT TITLE


SHEET TITLE




DESIGNED BY	
DRAWN BY	
CHECKED BY	
APPROVED BY	
SCALE	AS NOTED
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	

C-5.2


1-1 RAMONA STORMWATER TREATMENT SECTION
NOT TO SCALE




2-2 RAMONA STORMWATER TREATMENT SECTION
NOT TO SCALE




3-3 MISSION STORMWATER TREATMENT SECTION
NOT TO SCALE




4-4 MISSION STORMWATER TREATMENT SECTION
NOT TO SCALE




5-5 WALNUT STORMWATER TREATMENT SECTION
NOT TO SCALE




6-6 WALNUT STORMWATER TREATMENT SECTION
NOT TO SCALE





2' CURB CUT DETAIL
NOT TO SCALE



1 WEIR SECTION
NOT TO SCALE



CONCRETE ENERGY DISSIPATION STRUCTURE
NOT TO SCALE



RAMONA BIKE PATH DRIVEWAY GRADING AND STORMWATER TREATMENT DETAIL
SCALE: 1"=10'



GENERAL NOTES

- CODE COMPLIANCE: ALL WORK SHALL CONFORM TO AND BE PERFORMED IN ACCORDANCE WITH CODES, STANDARDS, AND ORDINANCES AS SET FORTH BY THE AUTHORITIES HAVING JURISDICTION AND THEIR LATEST ADOPTED EDITIONS (IN EFFECT AT TIME OF BUILDING PERMIT APPLICATION) OF THE FOLLOWING PUBLICATIONS:
 - CALIFORNIA CODE OF REGULATIONS TITLE 24, INCLUDES 2019 CALIFORNIA ELECTRICAL CODE, 2019 CALIFORNIA FIRE CODE, 2019 CALIFORNIA BUILDING CODE, ETC. WITH LOCAL AMENDMENTS AS APPLICABLE.
- SAFETY: THE ELECTRICAL CONTRACTOR IS RESPONSIBLE TO MAINTAIN ALL EQUIPMENT IN A SAFE AND RESPONSIBLE MANNER. KEEP DEAD FRONT EQUIPMENT IN PLACE WHILE EQUIPMENT IS ENERGIZED. CONDUCT ALL CONSTRUCTION OPERATIONS IN A SAFE MANNER FOR EMPLOYEES AS WELL AS OTHER WORKPERSONS OR ANYONE VISITING THE JOB SITE. PROVIDE BARRIERS, FLAGS, TAPE, ETC. AS REQUIRED FOR SAFETY. THE CONTRACTOR SHALL HOLD ALL PARTIES HARMLESS OF NEGLIGENCE SAFETY PRACTICES, WHICH MAY CAUSE INJURY TO OTHERS ON OR NEAR THE JOB SITE.
- LABEL PANELS, CABINETS, BACKBOARDS, MAIN DEVICES, SAFETY SWITCHES, CONTACTORS AND OTHER SPECIFICALLY DESIGNATED EQUIPMENT SHOWN ON PLANS. USE ENGRAVED LAMINATED PLASTIC NAMEPLATES ATTACHED BY SCREWS OR RIVETS. FOR FEEDERS, NEATLY AND INDISTINGUISHABLY LABEL CONDUIT DESTINATIONS ON BOTH VISIBLE ENDS OF CONDUIT RUNS WHERE CONDUITS TERMINATE AT DESIGNATED ENCLOSURES, STRUCTURES OR EQUIPMENT (INCLUDING PULL AND SPLICE BOXES).
- ALL CONDUCTORS SHALL BE COPPER WITH TYPE THHN/THWN INSULATION UNLESS OTHERWISE NOTED.
- ALL SWITCHES, CIRCUIT BREAKERS AND OTHER EQUIPMENT, AS SPECIFIED, SHALL HAVE TERMINATION PROVISIONS LISTED AND IDENTIFIED FOR USE WITH 75 DEG. CONDUCTORS, AND ALL FEEDER CONDUCTORS, AND CONDUITS, ARE SIZE BASED ON USE OF 75 DEG. C COPPER WIRES TYPE THWN/THHN.
- DEVICE LOCATIONS SHOWN ARE SCHEMATIC AND APPROXIMATE. EXACT LOCATIONS SHALL BE FIELD VERIFIED DURING POLY-CH-IN WITH ARCHITECTURAL ELEVATIONS, CASWORK SHOP DRAWINGS, FURNITURE, ETC. AND SHALL BE COORDINATED WITH OTHER TRADES TO AVOID CONFLICT WITH OTHER EQUIPMENT.

LEGEND

NOTE: INTERPRET IN CONTEXT

LIGHT FIXTURES

- CEILING SURFACE MOUNT
- WALL SURFACE MOUNT
- PENDANT MOUNT
- RECESSED DOWNLIGHT
- RECESSED WALLWASH
- RECESSED FLOOR
- SURFACE FLOOR
- FLOOR STRIP LIGHT
- TRACK LIGHT
- DIRECTIONAL FLOOD
- EMERGENCY FIXTURE
- POLE LIGHT
- POLE LIGHT-DECORATIVE
- TANDEM WIRED LAMPS
- SOLAR
- EXIT LIGHT-WALL
- EXIT LIGHT-CEILING
- ARROW INDICATES DIRECTION
- LETTER ADJACENT INDICATES FIXTURE TYPE

POWER/COMM.

- SINGLE RECEPT
- DUPLEX RECEPT
- GROUND FAULT CIRCUIT INTERRUPT
- DUAL LEVEL SWITCHING
- DUPLEX-HALF SWITCHED
- DOUBLE DUPLEX
- SPECIAL CONFIGURATION
- DUPLEX-FLOOR OUTLET
- JUNCTION BOX
- TELEPHONE OUTLET
- DATA OUTLET
- PHONE/DATA COMBO OUTLET
- MOUNTED ABOVE COUNTER
- SAFETY DISCONNECT
- TELEVISION OUTLET

CONDUIT/WIRE

- NEW
- UNDERGROUND
- NEW POWER HOMERUN (HOTS & NEUT SHOWN)
- ISOLATED GROUND
- EXISTING TO REMAIN
- (E) POWER HOMERUN
- CONDUIT STUB (W/MARKER)
- VERTICAL CONDUIT RUN
- CONDUIT SEAL
- FLEXIBLE CONNECTION
- LOW VOLTAGE
- SURFACE MOUNT RACEWAY

SWITCHES


- SPST
- DPST
- 3-WAY
- 4-WAY
- TRIP SWITCH
- THERMAL OVERLOAD
- WIPILOT LIGHT
- KEY OPERATED
- DUAL LEVEL SWITCHING
- SWITCH-LEG DESIGNATION
- OCCUPANCY SENSOR

MISCELLANEOUS


- MOTOR
- THERMOSTAT
- CIRCUIT BREAKER
- FUSIBLE SWITCH
- PHASE
- GROUND
- AMPERE
- AMP FUSE RATING
- ABOVE FINISH FLOOR
- ABOVE FINISH GRADE
- AMPERES INTERRUPT CAPACITY
- AMP SWITCH RATING
- BELOW FINISH GRADE
- CIRCUIT BREAKER
- CA. ELECTRICAL CODE
- CIRCUIT
- CONDUIT
- CONDUIT ONLY
- EXISTING
- ELECTRICAL CONTRACTOR
- EXHAUST FAN
- (E) IN (N) LOCATION
- (E) TO BE (R)
- FUTURE
- FIRE ALARM
- FACP FIRE ALARM CONTROL PANEL
- GROUNDING CONDUCTOR
- GENERAL CONTRACTOR
- GROUND FAULT CIRT INTERRUPTER
- GROUND
- GALVANIZED RIGID STEEL
- GANGED WITH SWITCH
- ISOLATED GROUND
- LIGHTING
- MECHANICAL CONTRACTOR
- MAIN CIRCUIT BREAKER
- MAIN LUGS ONLY
- MAIN SWITCHBOARD
- NOT IN CONTRACT
- NOT
- PHOTOVOLTAC
- RELOCATED
- TO BE REMOVED
- TYPICAL
- UNDER CABINET
- UNDERGROUND
- UNLESS OTHERWISE NOTED
- VOLT
- VOLT AMPERES
- WATT WIRE
- WEATHERPROOF (NEMA 3R)

SINGLE LINE DIAGRAM NOTES

- ALL CONDUCTORS SHALL BE COPPER WITH TYPE THHN/THWN INSULATION UNLESS OTHERWISE NOTED.
- EXPOSED CONDUIT SHALL BE GALVANIZED RIGID CONDUIT. BURIED CONDUIT MAY BE SCHEDULE 80 PVC AS ALLOWED BY CEC.
- ALL SWITCHES, CIRCUIT BREAKERS AND OTHER EQUIPMENT, AS SPECIFIED, SHALL HAVE TERMINATION PROVISIONS LISTED AND IDENTIFIED FOR USE WITH 75 DEG. CONDUCTORS, AND ALL FEEDER CONDUCTORS, AND CONDUITS, ARE SIZE BASED ON USE OF 75 DEG. C COPPER WIRES TYPE THWN/THHN.
- ALL EQUIPMENT SHALL HAVE AN APPROVED TESTING LABORATORY LABEL ATTACHED (UL, CSA, ETC.) (CEC 110-2).
- PER CALIFORNIA TITLE 24 SECTION 130.5, WIRING PROVISIONS HAVE BEEN MADE FOR DESEGREGATION OF THE ELECTRICAL CIRCUITS. THE OPTIONAL METERING HAS NOT BEEN PROVIDED FOR THIS PROJECT.



CHORRO UNDERPASS SINGLE LINE DIAGRAM



CHORRO UNDERPASS LIGHTING CONTROL BLOCK DIAGRAM

REFERENCE NOTES

- 3" C.O. FOR PG&E SECONDARY. ROUTE EXISTING WOOD POLE. CONFIRM WITH PG&E HANDOUT PACKAGE.
- METER PEDESTAL. 316 STAINLESS STREET. MYERS MEUC32-S OR EQUAL.
- 4 CIRCUIT ASTRONOMIC TIME CLOCK AND LIGHTING CONTACTOR. INTERMATIC ET284SCP.
- FENCE BACK LIGHTING 24VDC POWER SUPPLY AND CONTROLLER WITH DMX COLOR CONTROL. FRESKO PART # FCS-7-DMX.
- #3-1/2 PULL BOX PER CITY STANDARDS.
- 2" C. 2810 THWN & 1810 GND.
- 2" C. WITH PULL ROPE.
- 1" C. - 1 SPR#16 TSP FOR BACKLIGHT DMX SIGNAL & 1PR#16 FOR 24VDC POWER TO DFI BOX.
- 1" C. - SPARE (PULL ROPE ONLY).
- IRRIGATION CONTROLLER PER LANDSCAPE PLANS.
- 2" C. FOR IRRIGATION CONTROL CABLES.
- SEE WIRING BLOCK DIAGRAM FROM ADDITIONAL CONDUIT DETAILS.

REFERENCE NOTES

- 4 CIRCUIT ASTRONOMIC TIME CLOCK AND LIGHTING CONTACTOR. INTERMATIC ET284SCP.
- FENCE BACK LIGHTING 24VDC. 20W POWER SUPPLY.
- DMX512 CONTROLLER WITH COLOR CONTROL. FRESKO PART # FCS-7-DMX.
- CAT6 ETHERNET CABLE. 300VAC RATED INSULATION.
- DP512 4-WAY SPLITTER. HYDREL PART # DP4WHYD.
- #3-1/2 PULL BOX PER CITY STANDARDS. TYPICAL.
- 2" C. 2810 THWN & 1810 GND.
- 2" C. WITH PULL ROPE.
- (2) 1" C. - FOR FUTURE BACKLIGHT DMX SIGNAL AND SPARE. PROVIDE PULL ROPE IN EACH.
- 2" C. & (2) 1" C. SPARE CONDUITS WITH PULL ROPES.

ARC FLASH LABEL NOTES


- PER NEC 110.24 AND 110.21 PROVIDE LABELS ON ELECTRICAL SERVICE EQUIPMENT INDICATING MAXIMUM AVAILABLE FAULT CURRENT AND DATE OF FAULT CURRENT CALCULATION. REFER TO LABELING DETAILS, THIS SHEET.
- PER NEC 110.16 AND 110.21 PROVIDE LABELS AND MARKINGS ON ELECTRICAL DISTRIBUTION EQUIPMENT (I.E. SWITCHBOARDS, PANELBOARDS) INDICATING POTENTIAL ARC FLASH HAZARDS. REFER TO LABELING DETAILS, THIS SHEET.

FAULT CURRENT LABEL



INSTALL PERMANENT LABELS AT ALL NEW AND MODIFIED SWITCHBOARDS, DISTRIBUTION AND BRANCH PANELBOARDS AND DISCONNECT SWITCHES.

LABELING DETAILS



ACTUAL CALCULATED FAULT CURRENT
ACTUAL DATE OF FAULT CURRENT CALCULATION

OTTO ELECTRICAL

OTTO ELECTRICAL, INC.
SAN LUIS OBISPO, CA
GOTTO@OTTOELECTRICAL.COM
805.493.4329



CERRO SAN LUIS GREENWAY

ELECTRICAL NOTES, LEGEND, AND SINGLE LINE DIAGRAM

PROJECT TITLE

SHEET TITLE

DESIGNED BY:

DRAWN BY:

CHECKED BY:

APPROVED BY:

SCALE:

AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO.


PLAN FILE NO. / LOCATION

SHEET NO.


E-0.1



REFER TO CITY STANDARD
DETAILS 6010, 6020, 6030, 6040
FOR ADDITIONAL TRENCH AND
LOCATION REQUIREMENTS



LIGHTING CIRCUIT TRENCH DETAIL



OTTO | ELECTRICAL

OTTO ELECTRICAL, INC.
SAN LUIS OBISPO, CA
GOTTO@OTTOELECTRICAL.COM
805.498.4329



CERRO SAN LUIS GREENWAY

ELECTRICAL PLANS - BIKE PATH

PROJECT TITLE

SHEET TITLE

DESIGNED BY:

DRAWN BY:

CHECKED BY:

APPROVED BY:

SCALE:

DATE:

CITY SPECIFICATION NO.

PLAN FILE NO. / LOCATION

SHEET NO.

E-1.1



CERRO SAN LUIS GREENWAY

ELECTRICAL PLAN - CHORRO UNDERPASS

PROJECT TITLE

SHEET TITLE

DESIGNED BY:

DRAWN BY:

CHECKED BY:

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO.


PLAN FILE NO. / LOCATION

SHEET NO.


E-1.2




CHORRO CROSSING TRENCH DETAIL



SECONDARY TRENCH DETAIL



LIGHTING CIRCUIT TRENCH DETAIL



CHORRO UNDERPASS

OTTO | ELECTRICAL

REGISTERED PROFESSIONAL ENGINEER
GARRETT D. D.
20833
EXP. 9-30-22
ELECTRICAL
STATE OF CALIFORNIA

OTTO ELECTRICAL, INC.
SAN LUIS OBISPO, CA
GOTTO@OTTOELECTRICAL.COM
805.499.4329

WELO CERTIFICATION OF COMPLIANCE

THIS LANDSCAPE PLAN, WHEN INSTALLED, WILL COMPLY WITH THE COUNTY OF SAN LUIS OBISPO MUNICIPAL CODE AND THE WATER CONSERVATION MANDATE "WATER EFFICIENT LANDSCAPE ORDINANCE" (WELO) PREPARED IN ACCORDANCE WITH THE WATER EFFICIENT LANDSCAPE WORK SHEETS APPENDIX A AND APPENDIX B. THE WUCOL VALUES WERE GIVEN IN THE PLANT APPENDICES LOCATED IN THE RICE RANCH SPECIFIC PLAN DESIGN GUIDELINES AND ARE USED TO DETERMINE PF (PLANT FACTOR) VALUE IN THE CALCULATION IN THE CONSTRUCTION DOCUMENT PHASE.

THE WATER CONSERVATION METHOD FOR THE NEW LANDSCAPE PLANT MATERIAL WILL HAVE A LOW TO LOW/MED PF (PLANT FACTOR) RATING AND THE ETWU (ESTIMATED TOTAL WATER USE) PER YEAR IS ESTIMATED TO BE WITHIN THE MAXIMUM ALLOWABLE WATER ALLOCATION (MAWA) WHICH WILL BE CALCULATED FOR THE PROJECT. ADDITIONALLY, A "SMART" CONTROLLER WITH A CLIMATE CONTROL WEATHER STATION WILL BE USED TO MONITOR THE IRRIGATION WATER AND PRO-RATE DAILY WATER CONSUMPTION TO THE MINIMUM REQUIREMENTS FOR EACH HYDROZONE. ALL TREES WILL BE IRRIGATED ON SEPARATE SYSTEMS SO THAT ONCE ESTABLISHED, WATER CAN BE REGULATED IN A MORE EFFICIENT MANNER.

x *Mel Mills*

MELANIE MILLS, LANDSCAPE ARCHITECT R/LA NO. 5394

WATER CALCULATIONS

	San Luis Obispo
	Maximum Applied Water Allowance / Estimated Total Water Use

Non-Residential/Potable Water	
43.8 GPD (inches/year)	
6390 (Overhead Landscape Area (sq'))	
3650 (Ons Landscape Area (sq'))	
10.045	

Hydrozone	Plant Water Use (inches/year, sqft)	Plant Factor (PF)	Hydrozone Area (HA, sq')	Water Irrigation Type	(PF x HA x 4.5) / 100
Zone 1	1.0	1.0	630	Spring Irrigation	174.45
Zone 2	1.0	1.0	3650	Ons Irrigation	1382.86
Zone 3					
Zone 4					
Zone 5					
Zone 6					
Zone 7					
Zone 8					
Zone 9					
Zone 10					
Zone 11					
Zone 12					
Zone 13					
Zone 14					
Zone 15					
Zone 16					
Zone 17					
Zone 18					
Zone 19					
Zone 20					
HA			10.045		3657.56
Total LA			10.045		

MAWA:	122,751.3	ETWU complies with MAWA
ETWU:	83,899.4	
	11.45 GPD (unlimited Outdoor Flow) per year	
	6,250.00 gals per year	

IRRIGATION NOTES

- CONTRACTOR SHALL SLEEVE ALL LATERALS AND MAINLINES RUNNING UNDER PAVING. PIPE SLEEVE SIZE SHALL ALLOW FOR IRRIGATION TYPING AND RELATED COUPLINGS TO EASILY SLIDE THROUGH SLEEVING MATERIAL. EXTEND SLEEVES MINIMUM 18 INCHES BEYOND EDGES OF PAVING OR CONSTRUCTION.
- IRRIGATION PLAN IS DIAGNOSTIC. FINAL LOCATION OF PIPING WILL BE DETERMINED AT THE TIME OF INSTALLATION. MAINLINE AND LATERALS SHALL BE PLACED IN THE SAME TRENCH WHEN POSSIBLE. ALL G.C. VALVES ARE TO BE LOCATED 12" FROM SIDEWALKS, CURBS, ASPHALT & CONCRETE SURFACES.
- ALL EQUIPMENT REQUIRED BUT NOT SPECIFIED ON THE DRAWING, TO COMPLETE THE WORK, SHALL BE PROVIDED BY THE IRRIGATION CONTRACTOR.
- INSTALL ALL EQUIPMENT IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS AND/OR SPECIFICATIONS.
- CONTRACTOR SHALL COORDINATE POWER TO CONTROLLERS AND DEDICATE ONE (1) 20 AMP BREAKER FOR EACH CONTROLLER. THE AUTHORIZED REPRESENTATIVE SHALL REVIEW CONTROLLER LOCATIONS PRIOR TO INSTALLATION. 120 VOLT SERVICE AND HOOK-UP TO THE CONTROLLER SHALL BE COMPLETED BY A LICENSED ELECTRICAL CONTRACTOR. THIS COST IS TO BE A PART OF THE LANDSCAPE CONTRACTOR'S BID.
- CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE PLANS AND SITE CONDITIONS. PRIOR TO BEGINNING WORK, SHOULD CONFLICTING INFORMATION BE FOUND ON THE PLANS, THE CONTRACTOR SHALL NOTIFY THE PROJECT LANDSCAPE ARCHITECT BEFORE PROCEEDING WITH THE WORK IN QUESTION.
- DO NOT WILLFULLY INSTALL THE IRRIGATION SYSTEM AS SHOWN ON THE DRAWINGS WHEN IT IS OBVIOUS IN THE FIELD THAT OBSTRUCTIONS, PLANT MATERIAL SPACING, GRADE DIFFERENCES OR DIFFERENCES IN THE AREA DIMENSIONS EXIST THAT MIGHT NOT HAVE BEEN CONSIDERED IN THE ENGINEERING. SUCH OBSTRUCTIONS OR DIFFERENCES SHOULD BE BROUGHT TO THE ATTENTION OF THE LANDSCAPE ARCHITECT. IN THE EVENT THE NOTIFICATION IS NOT PERFORMED, THE CONTRACTOR SHALL ASSUME FULL RESPONSIBILITY FOR ANY REVISIONS NECESSARY AT NO EXPENSE TO THE OWNER.
- CONTRACTOR SHALL ADJUST HEADS AS NEEDED TO MINIMIZE OVERSPRAY ONTO HARDSCAPE AREAS.
- WIRE BETWEEN CONTROLLER AND VALVES TO BE COLOR STRANDED AND NOT A 2-WIRE SYSTEM.
- SPlicing OF 24 VOLT WIRES WILL NOT BE PERMITTED EXCEPT IN VALVE BOXES. LEAVE A 24" COIL OF EXCESS WIRE AT EACH SPLICE. LABEL ALL WIRES WITH WATERPROOF MARKERS AT ALL SPLICES AND VALVE MANIFOLDS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR THE INSTALLATION OF ALL MATERIAL APPEARING ON PLAN.
- PROVIDE PVC SHUTOFF VALVE FOR EACH VALVE.
- ALL EXISTING UTILITIES, WATER LINES AND FIRE HYDRANTS SHALL REMAIN CONNECTED AND IN FULL CONTINUOUS OPERATION DURING AND FOLLOWING ALL CONTRACT WORK.
- CONTRACTOR SHALL MAKE ALL NECESSARY ADJUSTMENTS TO THE IRRIGATION SYSTEM FOLLOWING A PRECIPITATION TEST PER THE OWNER. ADJUSTMENTS SHALL INCLUDE BUT WILL NOT BE LIMITED TO: HEAD RELOCATION, CHANGING NOZZLES, AND ADJUSTING ARC PATTERNS TO ATTAIN 85% EFFICIENT UNIFORMITY AS REQUIRED BY THE OWNER.
- CONTRACTOR SHALL SLEEVE ALL PIPE CROSSINGS UNDER HARDSCAPE. ALL SLEEVES UNDER PAVING SHALL RECEIVE IDENTIFYING MARK ON TOP OF HARDSCAPE AT EDGE OF PLANTER TO INDICATE LOCATION OF SLEEVE. EXTEND ALL SLEEVES 18" BEYOND EDGE OF HARDSCAPE TOP.
- ALL NEW IRRIGATION BOXES AND ADDITIONAL BOXES SHALL BE LOCATED IN PLANTING AREAS 18" MIN. AWAY FROM ADJACENT PAVING AND 3' MIN. AWAY FROM IMMEDIATE BUILDING ENTRIES.
- EXTRA VALVE WIRES SHALL BE PROVIDED FOR EACH VALVE STATION NOT USED ON PROPOSED CONTROLLER. UNLESS OTHERWISE NOTED ON PLANS, VALVE WIRES SHALL BE EXTENDED AND LOCATED IN TWO (2) VALVE BOXES EACH LOCATED AT OPPOSITE ENDS OF THE PROJECT SITE.
- FOR ALL DRIP AREAS: CONTRACTOR TO INSTALL AIR RELIEF VALVES, OPERATION INDICATORS AND FLUSH VALVES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- FOR LANDSCAPE AREAS TO RECEIVE IRRIGATION, CONTRACTOR SHALL NOT INSTALL ANY PLANTING UNTIL THE FOLLOWING ARE COMPLETED: 1. THE IRRIGATION SYSTEM SHALL BE FULLY OPERATIONAL. 2. HYDROSTATIC PRESSURE TESTS SHALL BE PERFORMED ON MAIN AND LATERAL LINES. 3. ALL ZONES SHALL PASS A COVERAGE TEST. 4. CONTROLLERS SHALL BE FULLY OPERATIONAL.
- TREES NOT SERVICED BY IRRIGATION TO RECEIVE TEMPORARY TREE WATERING BAG, PER SPECIFICATIONS.


IRRIGATION SCHEDULE

SYMBOL	MANUFACTURER/MODEL	ARC	PSI	RADIUS
	HUNTER MP STRIP PROS-12-PRS40-CV-F	LCS	40	5'x15'
	HUNTER MP STRIP PROS-12-PRS40-CV-F	RCS	40	5'x15'
	HUNTER MP1000 PROS-12-PRS40-CV-F	90-21C	40	14'
	HUNTER MP1000 PROS-12-PRS40-CV-F	360	40	14'
	HUNTER MP2000 PROS-12-PRS40-CV-F	90-21C	40	19'
	RAIN BIRD RVS-8-C 1401	360	40	3'
SYMBOL	MANUFACTURER/MODEL/DESCRIPTION			
	PIPE TRANSITION POINT ABOVE GRADE PIPE TRANSITION POINT FROM PVC LATERAL TO DRIP TUBING			
	AREA TO RECEIVE DRIP EMITTERS RAIN BIRD XB-PC SINGLE OUTLET, PRESSURE COMPENSATING DRIP EMITTERS. FLOW RATES OF 0.5 GPH-BLUE, 1.0 GPH-BLACK, AND 2.0 GPH-RED. COMES WITH A SELF-PIERCING BARR 80 FT X BARR CUT IT			
SYMBOL	MANUFACTURER/MODEL/DESCRIPTION			
	RAIN BIRD PE18R-PRS-D ELECTRIC REMOTE CONTROL VALVE FOR RECLAIMED WATER APPLICATIONS WITH SCRUBBER MECHANISM AND PRESSURE RVS II AFTER			
	RAIN BIRD 44-LRC 1" BRASS QUICK-COUPLING VALVE, WITH CORROSION-RESISTANT STAINLESS STEEL SPRING, LOCKING THERMOPLASTIC RUBBER COVER, AND 2-PK" F RCHTY			
	MATICOR-NORCA 759C BRASS SHUT OFF BALL VALVE, 1/2" TO 4", TWO-PIECE BODY, BLOW-OUT PROOF STEM, CHROME PLATED SOLID BRASS BALL, THREADED, WITH PTFE SEALS. C X C. SAMP. SUP. AS MAIN INF. PIPE			
	SUPERIOR 3100 1" NORMALLY OPEN DESIGN, SOLID BRASS CONSTRUCTION, ELECTRIC.			
	FEBCO 825F IF 3/4" 1/2" NPT TO 1/2" NPT BRASS 1/2" CW PRP VENTUR CAISENSE CONTROLLER (CITY SPEC)			
	CAISENSE CONTROLLER (CITY SPEC)			
	CAISENSE TEE INSERTED FLOW SENSOR			
	WATER METER 3/4" EXISTING CITY SERVICE MAIN. NEW METER REQUIRED.			
	WATER METER 3/4" CITY'S POTABLE WATER SERVICE			

IRRIGATION LATERAL LINE: PVC SCHEDULE 40

IRRIGATION MAINLINE: PVC SCHEDULE 40

PIPE SLEEVE: DUCTILE IRON PIPE-CLASS 350



This document was created by an application that isn't licensed to use [dynamips](#).
Purchase a license to generate PDF files without this notice.



CERRO SAN LUIS GREENWAY

IRRIGATION NOTES AND SCHEDULE

PROJECT TITLE

SHEET TITLE



DESIGNED BY:

MM

DRAWN BY:

DK

CHECKED BY:

MM

APPROVED BY:

SCALE:
AS NOTED

DATE:
JUNE 2, 2022

CITY SPECIFICATION NO:
1000036

PLAN FILE NO. LOCATION:
1417-05-CU21

SHEET NO:


L1001




CERRO SAN LUIS GREENWAY
IRRIGATION PLAN

PROJECT TITLE:

SHEET TITLE:



DESIGNED BY:	MM
DRAWN BY:	DK
CHECKED BY:	MM
APPROVED BY:	
SCALE:	AS NOTED
DATE:	JUNE 2, 2022
QTY SPECIFICATION NO:	1000036
PLAN FILE NO / LOCATION:	1417-05-CU21
SHEET NO:	LI101




FERRINI [7+85 - 9+05]

1" = 20' HORIZONTAL SCALE



IRRIGATION NOTES:
SEE LI001 FOR IRRIGATION SCHEDULE AND NOTES.



BIKE PATH [10+00 - 15+32]

1" = 20' HORIZONTAL SCALE

IRRIGATION NOTES:
SEE U001 FOR IRRIGATION SCHEDULE AND NOTES.




CERRO SAN LUIS GREENWAY

IRRIGATION PLAN

PROJECT TITLE

SHEET TITLE




DESIGNED BY: MM
DRAWN BY: DK
CHECKED BY: MM
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
QTY SPECIFICATION NO: 1000036
PLAN FILE NO / LOCATION: 1417-05-CU21
SHEET NO:

LI102






CERRO SAN LUIS GREENWAY
IRRIGATION DETAILS

PROJECT TITLE
SHEET TITLE




DESIGNED BY: MM
DRAWN BY: DK
CHECKED BY: LM
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
QTY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO:



LI501




9 TRENCHING
1" = 1'-0"




8 TREE BUBBLER
3/4" = 1'-0"




5 TYPICAL DRIP TUBING LAYOUT
1 1/2" = 1'-0"




7 QUICK COUPLING VALVE IN BOX
1 1/2" = 1'-0"




6 DRIP FLUSH VALVE
1 1/2" = 1'-0"




9 REMOTE CONTROL VALVE
1" = 1'-0"




10 BALL VALVE
1" = 1'-0"



11 RIGID PVC TO DRILINE TRANSITION
3" = 1'-0"



12 TYPICAL DRIP TUBING LAYOUT
1 1/2" = 1'-0"



13 FLOW SENSOR
3/4" = 1'-0"




CERRO SAN LUIS GREENWAY
IRRIGATION DETAILS

PROJECT TITLE:
SHEET TITLE:




DESIGNED BY: MM
DRAWN BY: DK
CHECKED BY: LM
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
QTY SPECIFICATION NO: 1000036
PLAN FILE NO / LOCATION: 1417-05-CU21
SHEET NO:

LI502




2 DRIP ZONE CONTROL VALVE
1/2" = 1'-0" RRM-1417.05-18



1 DRIP AIR RELIEF VALVE IN BOX
3\"/>

PLANT SCHEDULE

TREES	BOTANICAL NAME	COMMON NAME	CONT	WUCOLS	QTY	DETAIL
	AESCULUS CALIFORNICA	CALIFORNIA BUCKEYE	15 GAL	VERY LOW	2	PER CITY STANDARDS DETAIL #8220
	AGONIS FLEXUOSA	PEPPERMINT TREE	15 GAL	LOW	8	PER CITY STANDARDS DETAIL #8220
	CALISTEMON VIMINALIS	WEeping BOTTLEBRUSH	15 GAL	LOW	7	PER CITY STANDARDS DETAIL #8220
	EUCALYPTUS TORQUATA	CORAL GUM	15 GAL	LOW	1	PER CITY STANDARDS DETAIL #8220
	LAGROSTROEMIA INDICA 'RED'	CRAPe MYRTLE	15 GAL	LOW	9	PER CITY STANDARDS DETAIL #8220
	PISTACIA CHINENSIS	CHINESE PISTACHE	15 GAL	LOW	21	PER CITY STANDARDS DETAIL #8220
	PLATANUS RACEMOSA	CALIFORNIA SYCAMORE	15 GAL	MODERATE	13	PER CITY STANDARDS DETAIL #8220
	QUERCUS TOMENTELLA	ISLAND LIVE OAK	15 GAL	LOW	2	PER CITY STANDARDS DETAIL #8220

GENERAL PLANTING NOTES

- THERE ARE TWO TYPES OF LANDSCAPE AREAS ON THESE PLANS:
 - BIORETENTION AREAS: RECEIVE A SPECIAL SOIL MIX AND COMPOST MULCH NOT BARK MULCH, PER PLANS AND SPECIFICATIONS.
 - CONVENTIONAL PLANTING AREAS: SOILS TO BE AMENDED WITH COMPOST AND MULCHED WITH BARK MULCH PER THE SPECIFICATIONS.
- CONTRACTOR SHALL SUBMIT LABELED REPRESENTATIVE PHOTOS OF ALL PLANT MATERIAL TREES AND GROUNDCOVERS. PHOTOS SHALL BE OF THE SPECIFIED CONTAINER SIZE. PHOTOS SHALL BE SUBMITTED AS A COMPLETE SUBMITTAL PACKAGE FOR REVIEW AND APPROVAL. INCLUDE PHOTOS OF ANY PROPOSED SUBSTITUTES, CLEARLY LABELED.
- PLANTED AREAS SHALL BE MAINTAINED PER SPECIFICATIONS.
- CONTRACTOR SHALL PROVIDE ALL LABOR, MATERIALS, AND EQUIPMENT NECESSARY TO FURNISH AND INSTALL PLANT MATERIAL AS SHOWN ON THE DRAWINGS AND AS DESCRIBED IN THE SPECIFICATIONS.
- PLANTING PLANS ARE DIAGRAMMATIC AND PLANT SCHEDULE ON THE DRAWINGS SHALL BE USED AS A GUIDE ONLY. CONTRACTOR SHALL TAKEOFF AND VERIFY SIZES AND QUANTITIES BY PLAN CHECK. NOTIFY PROJECT LANDSCAPE ARCHITECT OF ANY MAJOR DISCREPANCIES.
- ALL STRUCTURAL AND HARDSCAPE IMPROVEMENTS SHALL BE CONSTRUCTED AND FINISHED AHEAD OF PLANTING UNLESS DESIGNATED OTHERWISE ON THE DRAWINGS.
- ADJUST PLANT MATERIAL AS NECESSARY AROUND UTILITY LOCATIONS. NOTIFY LANDSCAPE ARCHITECT OF ANY MAJOR CONFLICTS OR NECESSARY ADJUSTMENTS.
- ALL WORK ON THE IRRIGATION SYSTEM INCLUDING OPERATIONAL TESTS, AND BACKFILLING OF TRENCHES SHALL BE COMPLETED AHEAD OF PLANTING.
- LOCATIONS OF ALL PLANT MATERIAL SHALL BE REVIEWED ON SITE BY LANDSCAPE ARCHITECT PRIOR TO PLANTING. OWNER OR LANDSCAPE ARCHITECT RESERVES THE RIGHT TO MAKE ANY ADJUSTMENTS, SUBSTITUTIONS, ADDITIONS, AND DELETIONS TO THE PLANT LAYOUT AS WORK PROGRESSES.
- ALL GROUNDCOVER SHALL BE TRIANGULARLY SPACED, UNLESS OTHERWISE NOTED.
- TREES TO BE PLANTED WITHIN TEN (10) FEET OF HARDSCAPE, UTILITIES, WALLS, OR STRUCTURES SHALL BE INSTALLED WITH A ROOT BARRIER.
- SOIL SHALL BE AMENDED PURSUANT TO AN AGRONOMIC SOILS REPORT, WITH INFILTRATION RATES, PRIOR TO PLANTING.
- REFER TO PLANTING DETAILS FOR ADDITIONAL INFORMATION.
- HEIGHT TO FIRST BRANCH ON ALL STREET TREES SHALL BE NO LESS THAN 5 FEET.

SHRUBS	BOTANICAL NAME	COMMON NAME	CONT	WUCOLS	QTY	DETAIL
⊙	ACHILLEA Y 'MOONSHINE'	MOONSHINE YARROW	1 GAL	LOW	52	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	AGAVE ATTENUATA 'NOVA'	BLUE FLAME AGAVE	1 GAL	LOW	36	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	DIPLOCLADUS AURANTIACUS	STICKY MONKEYFLOWER	1 GAL	VERY LOW	75	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	ERIOGONUM CROCATUM	SAFFRON BUCKWHEAT	1 GAL	LOW	16	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	ERIOGONUM FASCICULATUM 'WARRINER LYTLE'	WARRINER LYTLE CALIFORNIA BUCKWHEAT	1 GAL	LOW	4	PER CITY STANDARDS DETAIL #8410 & #8420
•	FESTUCA CALIFORNICA 'RIVER HOUSE BLUES'	RIVER HOUSE BLUES CALIFORNIA FESCUE	1 GAL	LOW	355	PER CITY STANDARDS DETAIL #8410 & #8420
•	FESTUCA MUELLERI	MUELLER'S FESCUE	1 GAL	LOW	306	PER CITY STANDARDS DETAIL #8410 & #8420
•	FESTUCA RUBRA 'MOLATE'	MOLATE RED FESCUE	1 GAL	LOW	35	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	FRANGULA CALIFORNICA 'MOUND SAN BRUNO'	MOUND SAN BRUNO COFFEEBERRY	5 GAL	LOW	14	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	IRIS DOUGLASSIANA	DOUGLAS IRIS	1 GAL	LOW	12	PER CITY STANDARDS DETAIL #8410 & #8420
•	JUNCUS PATENS 'ELK BLUE'	ELK BLUE CALIFORNIA GRAY RUSH	1 GAL	LOW	144	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	LEYMUS CONDENSATUS 'CANYON PRINCE'	NATIVE BLUE RYE	1 GAL	LOW	41	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	LOMANDRA CONFECTIONARIA 'POM POM'	SHORTY NAT RUSH	1 GAL	LOW	12	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	LOMANDRA LONGIFOLIA 'BREEZE TM'	BREEZE NAT RUSH	1 GAL	LOW	51	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	LOMANDRA LONGIFOLIA 'PLATINUM BEAUTY'	VAREGATED RUSH	1 GAL	LOW	5	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	LOMANDRA X LOMLON TM	LIME TUFF DWARF NAT RUSH	1 GAL	LOW	5	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	MISCANTHUS SINENSIS 'MORNING LIGHT'	MORNING LIGHT EULALIA GRASS	5 GAL	LOW	7	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	MUHLENBERGIA DUBIA	PINE MUHLY	1 GAL	LOW	97	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	MUHLENBERGIA RIGENS	DEER GRASS	1 GAL	LOW	55	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	MYRTICA CALIFORNICA	PACIFIC WAX MYRTLE	1 GAL	LOW	9	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	NEPETA X FAASSENII 'PURRSIAN BLUE'	PURRSIAN BLUE CATMINT	1 GAL	LOW	11	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	PARTHENOCISSUS QUINQUEFOLIA	VIRGINIA CREEPER	1 GAL	MODERATE	20	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	PENNISETUM SPATHULATUM	RYE PUFFS	1 GAL	LOW	44	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	PHLOMIS FRUTICOSA	JERUSALEM SAGE	1 GAL	LOW	10	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	RIBES SPECIOSUM	FUCHSIA FLOWERING GOOSEBERRY	1 GAL	LOW	21	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	ROSA CALIFORNICA 'ELSE'	CALIFORNIA WILD ROSE	1 GAL	LOW	22	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	SALVIA SPATHACEA	HUMMINGBIRD SAGE	1 GAL	LOW	55	PER CITY STANDARDS DETAIL #8410 & #8420
⊙	SESLERIA AUTUMNALIS 'CAMPO VERDE'	AUTUMN MOOR GRASS	1 GAL	MODERATE	28	PER CITY STANDARDS DETAIL #8410 & #8420



CERRO SAN LUIS GREENWAY

PLANTING SCHEDULE AND NOTES

PROJECT TITLE

SHEET TITLE



DESIGNED BY: MM
 DRAWN BY: DK
 CHECKED BY: MM
 APPROVED BY:
 SCALE: AS NOTED
 DATE: JUNE 2, 2022
 QTY SPECIFICATION NO: 1000036
 PLAN FILE NO: 1417-05-CU21
 SHEET NO:

LP001



PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
1	PLATANUS CHINENSIS	N 2305450.5827	E 5763811.8154
2	PLATANUS CHINENSIS	N 2305437.1832	E 5763790.7496
3	QUERCUS TOMENTELLA	N 2305427.6409	E 5763825.5042
4	PLATANUS CHINENSIS	N 2305403.8733	E 5763804.4504
5	PLATANUS CHINENSIS	N 2305399.3341	E 5763827.9705
6	PLATANUS CHINENSIS	N 2305376.5893	E 5763824.1131
7	QUERCUS TOMENTELLA	N 2305360.4987	E 5763866.7444
8	PLATANUS CHINENSIS	N 2305350.4443	E 5763884.2874
9	PLATANUS CHINENSIS	N 2305340.3379	E 5763895.1028
10	PLATANUS CHINENSIS	N 2305341.6409	E 5763884.1094
11	PLATANUS CHINENSIS	N 2305325.4496	E 5763901.2745
12	PLATANUS CHINENSIS	N 2305343.3025	E 5763913.8748
13	QUERCUS TOMENTELLA	N 2305351.9701	E 5763919.0044
14	QUERCUS TOMENTELLA	N 2305399.6802	E 5763923.2946
15	QUERCUS TOMENTELLA	N 2305379.3338	E 5763943.6749
16	QUERCUS TOMENTELLA	N 2305347.4450	E 5763943.0529
17	QUERCUS TOMENTELLA	N 2305360.9940	E 5763945.3200
18	QUERCUS TOMENTELLA	N 2305341.7601	E 5763987.6643
19	QUERCUS TOMENTELLA	N 2305319.1405	E 5764009.3350

NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.

ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.

TREE PLANTING NOTES

- AS PART OF TREE PLANTING, CONTRACTOR TO CARRYOUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
- WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXISTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
- WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
- MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
- WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL, AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.

FERRINI [7+85 - 9+05]

1" = 20' HORIZONTAL SCALE




CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE

SHEET TITLE



DESIGNED BY

MM

DRAWN BY

DK

CHECKED BY

MM

APPROVED BY

SCALE

AS NOTED

DATE

JUNE 2, 2022

QTY SPECIFICATION NO.


1000036

PLAN FILE NO. LOCATION

1417-05-CU21

SHEET NO.

LP101



BIKE PATH [10+00 - 15+32]

1" = 20' HORIZONTAL SCALE



GRANT DEED AND ROW AGREEMENT

- Deed Section 2 - Restoration of Grantor Property: Contractor to restore areas impacted by construction within the Temporary Easement Area located on the Church of Jesus Christ of Latter-day Saints ("Grantor") property to pre-construction condition upon completion of construction activities. This includes, but is not limited to removal of all equipment and materials; repair of any damage; and replacement of topsoil, vegetation, mulch, etc.
- Deed Section 5.3 - Use of Easement Area: Contractor shall not carry out any activities that create nuisances or pose risks to the Grantor, including but not limited to noises, odors, light, dust, smoke, gases, light, vibration, risk of fire, explosion, or hazardous materials.
- ROW Agreement - Section E: Contractor to reinstall the 6' high metal security fence, or a comparable replacement fence, along Foothill Boulevard and for the length of the property line between the Grantor's property and the new Easement Area.
- ROW Agreement - Section E: As part of the construction project, the Contractor plant eight trees within the Temporary Construction Easement located on the Grantor's property.
- Contractor to comply with the full requirements described in the Deed and Right of Way Agreement, which are provided as an attachment to the Bid Documents.

TREE PLANTING NOTES

- AS PART OF TREE PLANTING, CONTRACTOR TO CARRY OUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
- WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXISTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
- WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
- MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
- WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.

PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
20	PISTACIA CHINENSIS	N 2303924.6434	E 5763849.4662
21	PISTACIA CHINENSIS	N 2303923.9319	E 5763872.9528
22	PISTACIA CHINENSIS	N 2303923.4638	E 5763896.2805
23	PISTACIA CHINENSIS	N 2303919.2343	E 5763940.0254
24	LAGERSTROEMIA INOICA 'RED'	N 2303780.4088	E 5763908.1933
25	LAGERSTROEMIA INOICA 'RED'	N 2303759.5473	E 5763907.2340
26	LAGERSTROEMIA INOICA 'RED'	N 2303705.1542	E 5763905.1142
27	LAGERSTROEMIA INOICA 'RED'	N 2303688.1467	E 5763904.0254
28	LAGERSTROEMIA INOICA 'RED'	N 2303637.8371	E 5763904.1429
29	PLATANUS RACEMOSA	N 2303576.4446	E 5763900.0293
30	LAGERSTROEMIA INOICA 'RED'	N 2303550.1028	E 5763899.1805
31	LAGERSTROEMIA INOICA 'RED'	N 2303529.8231	E 5763899.3181
32	LAGERSTROEMIA INOICA 'RED'	N 2303522.3489	E 5763875.9174

NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.

ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.

BIORETENTION PLANTING NOTES

- TREES SHALL BE LOCATED AT LEAST 2.5 FEET FROM FACE OF CURB.
- TREES SHALL BE LOCATED AT LEAST 5 FEET FROM BIORETENTION AREA INLETS AND BACK FROM CONVEYANCE CHANNELS TO AVOID SCOURING OF ROOT BALLS.
- DO NOT PLANT GRASSES OR SHRUBS IN FRONT OF CURB CUT INLETS, WHERE THEY WILL BLOCK CONVEYANCE FROM ENTERING BIORETENTION PLANTER.
- BIORETENTION AREAS RECEIVE COMPOST MULCH, NOT BARK MULCH, PER PLANS AND SPECIFICATIONS.

LEGEND

- CONCRETE PAVERS
- BENCH
- TRASH RECEPTACLE



CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE

SHEET TITLE



DESIGNED BY

MM

DRAWN BY

DK

CHECKED BY

MM

APPROVED BY

AS NOTED

SCALE

JUNE 2, 2022

DATE

QTY SPECIFICATION NO.


1000336

PLAN FILE NO. LOCATION

1417-05-CU21

SHEET NO.

LP102



NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.

ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.

TREE PLANTING NOTES

1. AS PART OF TREE PLANTING, CONTRACTOR TO CARRYOUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
2. WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXSTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
3. WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
4. MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
5. WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL, AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.

PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
33	AGONIS FLEXUOSA	N 2303443.0612	E 5764173.9277
34	AGONIS FLEXUOSA	N 2303442.0000	E 5764203.3693
35	AGONIS FLEXUOSA	N 2303441.3243	E 5764231.8772
36	AGONIS FLEXUOSA	N 2303439.7822	E 5764307.2822
37	AGONIS FLEXUOSA	N 2303437.8692	E 5764375.1625



CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE

SHEET TITLE



DESIGNED BY: MM

DRAWN BY: DK

CHECKED BY: MM

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036


PLAN FILE NO: LOCATION: 1417-05-CU21

SHEET NO:

LP103


PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
38	PISTACIA CHINENSIS	N 2301887.7684	E 5744539.5634
39	CALLISTEMON Viminalis	N 2301896.1149	E 5744602.3414
40	PISTACIA CHINENSIS	N 2301903.9994	E 5744703.0427
41	PISTACIA CHINENSIS	N 2301907.4028	E 5744728.3494
42	QUERCUS TOMENTELLA	N 2301936.9050	E 5744891.7904
43	QUERCUS TOMENTELLA	N 2301940.2419	E 5744920.0801



MISSION [10+00 - 13+75]

1" = 20' HORIZONTAL SCALE



MISSION [13+75 - 18+25]

1" = 20' HORIZONTAL SCALE

NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.

ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.

BIORETENTION PLANTING NOTES

1. TREES SHALL BE LOCATED AT LEAST 2.5 FEET FROM FACE OF CURB.
2. TREES SHALL BE LOCATED AT LEAST 5 FEET FROM BIORETENTION AREA INLETS AND BACK FROM CONVEYANCE CHANNELS TO AVOID SCOURING OF ROOT BALLS.
3. DO NOT PLANT GRASSES OR SHRUBS IN FRONT OF CURB CUT INLETS, WHERE THEY WILL BLOCK CONVEYANCE FROM ENTERING BIORETENTION PLANTER.
4. BIORETENTION AREAS RECEIVE COMPOST MULCH, NOT BARK MULCH, PER PLANS AND SPECIFICATIONS.

TREE PLANTING NOTES

1. AS PART OF TREE PLANTING, CONTRACTOR TO CARRYOUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
2. WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXISTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
3. WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
4. MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
5. WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL, AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.



CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE

SHEET TITLE



DESIGNED BY: MM

DRAWN BY: DK

CHECKED BY: MM

APPROVED BY:

SCALE: AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

LP104



PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
52	CALLISTEMON VIMINALIS	N 2301158.4949	E 5765415.8187
53	CALLISTEMON VIMINALIS	N 2301108.3527	E 5765430.4924
54	CALLISTEMON VIMINALIS	N 2301081.8205	E 5765438.6797
55	CALLISTEMON VIMINALIS	N 2301073.4935	E 5765393.4066
56	PISTACIA CHINENSIS	N 2301017.7432	E 5765458.2834
57	EUCALYPTUS TOROJATA	N 2300876.8872	E 5765472.1286
58	CALLISTEMON VIMINALIS	N 2300778.8972	E 5765596.4870
59	CALLISTEMON VIMINALIS	N 2300724.0531	E 5765632.7745
63	LAGERSTROEMIA INDICA RED	N 2300931.5121	E 5765541.1252


LEGEND

- CONCRETE PAVERS
- BENCH
- TRASH RECEPTACLE

NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.

ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.



TREE PLANTING NOTES

- AS PART OF TREE PLANTING, CONTRACTOR TO CARRYOUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
- WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXISTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
- WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
- MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
- WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL, AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.

CITY OF SAN LUIS OBISPO

CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE

SHEET TITLE

REGISTERED LANDSCAPE ARCHITECT

STATE OF CALIFORNIA

DESIGNED BY: MM

DRAWN BY: DK

CHECKED BY: MM

APPROVED BY:

SCALE: AS NOTED

DATE: JUNE 2, 2022

CITY SPECIFICATION NO: 1000036

PLAN FILE NO: 1417-05-CU21

SHEET NO:

LP106



CERRO SAN LUIS GREENWAY

LANDSCAPE PLAN

PROJECT TITLE



DESIGNED BY

MM

DRAWN BY

DK

CHECKED BY

MM

APPROVED BY

SCALE AS NOTED


DATE: JUNE 2, 2022

CITY SPECIFICATION NO. 1000308

PLAN FILE NO. LOCATION 1417-05-CU21

SHEET NO.

LP107



CHORRO [26+50 - 33+25]


1" = 20' HORIZONTAL SCALE



PROPOSED TREE COORDINATE LOCATIONS

POINT	DESCRIPTION	NORTHING	EASTING
60	PLATANUS RACEMOSA	N 2300479.8982	E 5765819.9165
61	ASCCULUS CALIFORNICA	N 2300214.1416	E 5765907.4388
62	ASCCULUS CALIFORNICA	N 2300118.0370	E 5765920.4522

LEGEND



EXISTING TREES AND SHRUBS

- APPROXIMATE LOCATION OF SHRUBS/TREES TO BE REMOVED SHOWN ON PLAN. REMOVE ROOTS PER SPECIFICATIONS.
- SHRUBS/TREES TO BE REMOVED WILL BE TAGGED IN THE FIELD BY PROJECT ARBORIST. CONTRACTOR TO PROVIDE LANDSCAPE ARCHITECT WITH 72 HOURS NOTICE, TO SCHEDULE ARBORIST TAGGING.
- CONTRACTOR TO RAISE CROWN ON EXISTING TREES TO REMAIN AS FOLLOWS:
 - 20' TREES OR SMALLER - REMOVE LIMBS UP TO 8'
 - TREES 20' TO 30' TALL - REMOVE LIMBS UP TO 10'
 - TREES OVER 30' TALL - REMOVE LIMBS UP TO 12'

NOTES

SEE LP001 FOR PLANTING SCHEDULE AND NOTES.
ONGOING ESTABLISHMENT AND MAINTENANCE OF ALL LANDSCAPE AREAS NOT COVERED BY IRRIGATION SYSTEMS TO BE CARRIED OUT BY OTHERS, PER SPECIFICATIONS.

BIORETENTION PLANTING NOTES

- TREES SHALL BE LOCATED AT LEAST 2.5 FEET FROM FACE OF CURB.
- TREES SHALL BE LOCATED AT LEAST 5 FEET FROM BIORETENTION AREA INLETS AND BACK FROM CONVEYANCE CHANNELS TO AVOID SCOURING OF ROOT BALLS..
- DO NOT PLANT GRASSES OR SHRUBS IN FRONT OF CURB CUT INLETS, WHERE THEY WILL BLOCK CONVEYANCE FROM ENTERING BIORETENTION PLANTER.
- BIORETENTION AREAS RECEIVE COMPOST MULCH, NOT BARK MULCH, PER PLANS AND SPECIFICATIONS.

TREE PLANTING NOTES


- AS PART OF TREE PLANTING, CONTRACTOR TO CARRYOUT ALL NEEDED DEMOLITION, EXCAVATION OF TREE PITS, PREPARATION OF SOILS, APPLICATION OF AMENDMENT IN PLANTING HOLE, INSTALLATION OF TREE STAKES, INSTALLATION AND CONNECTION OF IRRIGATION WHERE APPLICABLE, INSTALLATION OF TREE ROOT BARRIER WHERE APPLICABLE, PLACEMENT OF MULCH, AND WATER-IN TREE UPON FINAL PLANTING AS DESCRIBED ON PLANS AND IN SPECIFICATIONS.
- WHERE PROPOSED TREES ARE LOCATED IN A PAVED OR AGGREGATE SURFACE AREA, CONTRACTOR TO REMOVE EXISTING PAVING TO CREATE A THREE-FOOT BY THREE-FOOT (3' X 3') PLANTING PIT.
- WHERE PROPOSED TREES ARE NOT LOCATED IN A NEW AMENDED PLANTING AREA, OR BIORETENTION AREA, CONTRACTOR TO PREPARE THE EXISTING SOIL IN THE TREE PIT AS DESCRIBED IN THE PROJECT SPECIFICATIONS.
- MULCH NEW TREE PLANTINGS TO COVER FULL EXTENT OF TREE PIT, MULCH TYPE AND DEPTH PER SPECIFICATIONS.
- WHERE TREES ARE NOT COVERED BY IRRIGATION SYSTEM, CONTRACTOR TO PROVIDE, INSTALL, AND FILL AT INSTALLATION TREE WATERING BAGS, PER SPECIFICATIONS.



CERRO SAN LUIS GREENWAY
CONSTRUCTION DETAILS




DESIGNED BY: MM
DRAWN BY: DK
CHECKED BY: MM
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO: 1417-05-CU21
SHEET NO: LP501



5 BENCH IN UNIT PAVING
3/4" = 1'-0"


RRM-1417-05-81



NOTES:
1. REFER TO PLANS FOR LOCATIONS OF PERMEABLE VS. NON PERMEABLE PAVERS.
2. AIR VOL. BLOCK HOLLAND PAVERS, "RAILROAD BLEND" TUMBLER PAVERS, OR APPROVED EQUAL.
3. PATTERN: INSTALL IN "RUNNING BOND" PATTERN, WITH NON-BEVELED SIDE UP.
4. CUT NO LESS THAN 2" LONG OR WIDE.
5. SURFACE OF PAVES SET FLUSH WITH ADJACENT CURBS AND SIDEWALK.


4 CONCRETE PAVERS - PEDESTRIAN
1 1/2" = 1'-0"

RRM-1417-05-23



2 METAL PICKET FENCE AND GATE
1/2" = 1'-0"


RRM-1417-05-02



NEW PLASTER TO MATCH EXISTING PLASTERS ALONG ADJACENT CHURCH PROPERTY FRONTAGE.
NOTES: PRECISE DIMENSIONS TO MATCH EXISTING PLASTERS

3 CMU PILASTER
NTS


RRM-1417-05-01



NOTE: AMERISTAR MONTAGE I, GENESIS MODEL OR APPROVED EQUAL. VERIFY & INSTALL PER MANUFACTURER'S INSTRUCTIONS PRIOR TO FABRICATION. FENCE POST SIZE, POST SPACING, AND FOOTINGS PER MANUFACTURER'S SPECIFICATIONS. SUBMIT SHOP DRAWINGS FOR APPROVAL BY AUTHORIZED REPRESENTATIVE.
FENCE COLOR: TO BEST MATCH EXISTING FENCE COLOR
HEIGHT: MATCH EXISTING FENCE HEIGHT


1 HIGH CURB
NTS

RRM-1417-05-03



CURB END PANELS
PLAN VIEW

1. DG EXTENDS AT GAP BETWEEN COLUMN AND NEW CURB (TYPICAL)
2. 1/4" THICK 304 GALVANIZED STEEL PLATE (TYPICAL)
3. 2" DIA. WEEP HOLES - 2 PER SIDE. PROVIDE STAINLESS STEEL WASH AT BACK OF PLATE (TYPICAL)
4. ATTACH PLATE TO CONCRETE CURB WITH 2-1/2" DIA. TIE ROD ANCHOR BOLTS GALVANIZED FINISH, WITH MIN. EMBED OF 3-1/4". CONTRACTOR TO SPACE TO AVOID CONTACT WITH CURB REBAR (TYPICAL). MIN. 3" SPACING BETWEEN BOLTS, AND TO BE PROTECTED FROM EARTH BY WATERPROOFING LAYER.
5. SWALE LOW POINTS AT AGGREGATE TO ALLOW FLOW TO WEEP THROUGH GALVANIZED PLATE (TYPICAL)



CURB END PANEL AND DRAIN ROCK

1. PROVIDE FILL DEPTH DRAIN ROCK AT SWALE LOW POINTS. AT CURB ENDS TO ALLOW DRAINAGE TO ESCAPE THROUGH WEEP HOLES IN PLATE.
2. 2" DIA. WEEP HOLES - 2 PER SIDE (TYPICAL)

SYMBOLS				WALL TYPES		SHEET INDEX	
	DETAIL REFERENCE BUBBLE WITH LEADER		INDICATES SHEAR WALL TYPE AND LENGTH PER SHEAR WALL SCHEDULE		INDICATES TOP PLATE SPLICE NAILING PER SCHEDULE		INDICATES PLYWOOD SIDE FOR SHEAR WALL
	DETAIL REFERENCE BUBBLE		INDICATES SHEAR WALL STRAP / HOLDDOWN TYPE PER SCHEDULE		INDICATES BEARING WOOD WALL BELOW		INDICATES BEARING WOOD WALL ABOVE
	FULL HEIGHT SECTION INDICATOR		INDICATES SPAN AND DIRECTION OF ROOF RAFTER OR FLOOR JOIST WITH WEB STIFFENER		INDICATES NON-BEARING WOOD WALL BELOW		INDICATES NON-BEARING WOOD WALL ABOVE
	ELEVATION OF WALL OR FRAME		INDICATES SPAN AND DIRECTION OF ROOF RAFTER OR FLOOR JOIST		INDICATES EXISTING BEARING WOOD WALL		INDICATES EXISTING NON-BEARING WOOD WALL
	NORTH ARROW		INDICATES EXTENT OF FRAMING OR OTHER STRUCTURAL ELEMENT		INDICATES EXISTING NON-BEARING WOOD WALL		INDICATES BEARING CMU WALL BELOW
	TOP/BOTTOM OF ELEVATIONS		INDICATES HEADER @ OPENING PER HEADER SCHEDULE		INDICATES BEARING CMU WALL ABOVE		INDICATES NON-BEARING CMU WALL BELOW
	SLOPE		INDICATES SAND OR GROUT		INDICATES NON-BEARING CMU WALL ABOVE		INDICATES EXISTING BEARING CMU WALL
	WELDED WIRE FABRIC (WWF-LAYER)		INDICATES GRAVEL		INDICATES EXISTING NON-BEARING CMU WALL		INDICATES BEARING CONCRETE WALL BELOW
	STEPPED SURFACE, FLOOR DEPRESSION		STEEL IN CROSS SECTION		INDICATES BEARING CONCRETE WALL ABOVE		INDICATES NON-BEARING CONCRETE WALL BELOW
	SLOPED SURFACE		STEEL HSS TUBE COLUMN		INDICATES NON-BEARING CONCRETE WALL ABOVE		INDICATES EXISTING BEARING CONCRETE WALL
	STEPPED FOOTING		STEEL HSS OR PIPE COLUMN		INDICATES EXISTING NON-BEARING CONCRETE WALL		
	BOTTOM STEPPED FOOTING		WIDE FLANGE STEEL COLUMN				
			WOOD POST				

ABBREVIATIONS

A & B	ABOVE AND BELOW	4	FOUR (NAIL OR BAR DIA)	HGR	HANGER	PA	POST ABOVE	T & B	TOP AND BOTTOM
AB	ANCHOR BOLT	DBL	DOUBLE	HP	HIGH POINT	PARA OR //	PARALLEL	T & G	TONGUE & GROOVE
ABV	ABOVE	DEPT	DEPTH	HSH	HORIZONTALLY SLOTTED HOLES	PC	PRECAST-PIECE	TD	TOP OF
ACI	AMERICAN CONCRETE INSTITUTE	DET	DETAIL	HT	HIGHT	PDP	PENETRANT DEFECT	TOC	TOP OF CURB, TOP OF CONCRETE
ADOL	ADDITIONAL	DF	DOUGLAS FIR LARCH	ID	INSIDE DIAMETER	PI	PLYWOOD INDEX	TOF	TOP OF FOOTING
ADJ	ADJACENT	DIA OR Ø	DIAMETER	IF	INSIDE FACE	R OR PL	PLATE	TEMP	TEMPERATURE, TEMPORARY
AESS	ARCHITECTURAL EXPOSED STRUCTURAL STEEL	DIAG	DIAGONAL	I-JST	I-JOIST	PL	PROPERTY LINE	THRU	THROUGH
AISC	AMERICAN INSTITUTE OF STEEL CONSTRUCTION	DAPH	DAPHRAGM	IN	INCH	POND PER LINEAL FOOT	PLCS	PLACES	THICKNESS/THICK
ALT	ALTERNATE	DN	DOWN	INCL	INCLUDE	PLCS	PLACES	THR	THREADED
ALUM	ALUMINUM	DWG	DRAWING	INFO	INFORMATION	PLY	PLYWOOD	TOP or T	TOP
ANCH	ANCHOR	DWL	DOWEL	INSP	INSPECTION	PROCP	PROCESSED	TOF	TOP OF
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE	EA	EACH	INT	INTERIOR	PT	PRESSURE TREATED	TOW	TOP OF WALL
APA	ENGINEERED WOOD ASSOCIATION (FORMERLY THE AMERICAN PLYWOOD ASSOCIATION)	EF	EACH FACE	JST	JOIST	PW	PLATE WASHER	TS	TRIMMER STUD
APPVIO	APPROVED	EJ	EXPANSION JOINT	JT	JOINT	PXP	PARTIAL JOINT PENETRATION WELD	TVP	TYPICAL
APPROX	APPROXIMATE	EL	ELEVATION	K	KIPS	PREFAB	PREFABRICATED	UNO	UNLESS NOTED OTHERWISE
ARCH	ARCHITECTURAL ARCHITECT	ELEC	ELECTRICAL	KS	KING STUD	PSF	POUNDS PER SQUARE FOOT	UT	ULTRA-SONIC TEST
AWPA	AMERICAN WOOD PRESERVERS ASSOCIATION	ELEV	ELEVATOR	KP	KING POST	PSI	POUNDS PER SQUARE INCH	VERT	VERTICAL
AWS	AMERICAN WELDING SOCIETY	EMED	EMBLEMENT	KS	KIPS PER SQUARE INCH	PSL	PARALLEL STRAND LUMBER	VSH	VERTICAL SLOTTED HOLES
ATC	AMERICAN INSTITUTE OF TIMBER CONSTRUCTION	EN	EDGE NAIL	LB(S) OR #	POUNDS	PVMT	PAVEMENT	WH	WHERE
ASTM	AMERICAN SOCIETY FOR TESTING MATERIALS	ENGR	ENGINEER	LF	LINEAL FOOT	#	POUND NUMBER	W/O	WITHOUT
BLDG	BUILDING	EQ	EQUAL OR EQUIVALENT	LIN	LINEAL LINEAR	REF	REFERENCE	WO	WHERE OCCURS
BLK	BLOCK	EQU	EQUIPMENT	LIV	LONG LEG HORIZONTAL	RENF	REINFORCE, REINFORCING	WO	WOOD
BLG	BLOCKING	EQP	EQUIPMENT	LIV	LONG LEG VERTICAL	REQD	REQUIRED	WP	WORK POINT, WATERPROOF
BM	BEAM	ES	EACH SIDE	LP	LOW POINT	RF	ROOF	WWF	WELDED WIRE FABRIC
BN	BOUNDARY NAIL	EW	EACH WAY	LSH	LONG SLOTTED HOLES	R	ROOF RAFTER		
BOT OR B	BOTTOM	EXT or (E)	EXTENDING	LVL	LAMINATED VENEER LUMBER	Ø	ROUND DIAMETER		
BRG	BRACE	EXT	EXTENDING	LWT	LIGHTWEIGHT	SCHED	SCHEDULE	W	W SHAPE
BRG	BEARING	EXT	EXTENDING	LVL	LEVEL OR LAMINATED VENEER LUMBER	SECT	SECTION	C	AMERICAN STD CHANNEL SHAPE
BWV	BETWEEN	FN	FINISH	MAS	MASONRY	SFP	SEPARATION	MC	MISC CHANNEL SHAPE
CANT	CANTILEVER	FON	FOUNDATION	MEB	MACHINE BOLT	SHT	SHEATH	L	ANGLE SHAPE
CAM OR C	CAMBER	FR	FLOOR	MFR	MECHANICAL	SHT	SHEATH	WT, LT, MT	STRUCTURE SHAPE
CC	CENTER TO CENTER	FLG	FLOOR	MIN	MINIMUM	SHTG	SHEATHING	PPE	STANDARD PPE SHAPE
CG	CENTER OF GRAVITY	FR	FLOOR	MIS	MISCELLANEOUS	SM	SIMILAR	PPE-X	EXTRA STRONG PPE SHAPE
CP	CASE-IN-PLACE	FT	FOOT, FEET	MS	MISCELLANEOUS	SO	SLAB ON GRADE	PPE-V	VERTICAL PPE SHAPE
CJ	CONSTRUCTION JOINT, CONTROL JOINT	FT	FOOT, FEET	N	NUMBER	SPL	SPACING	HS	HOLLOW STRUCTURAL SECTION
CL	CENTER LINE	FT	FOOT, FEET	NO or #	NUMBER	SPL	SPACING		
CLR	CLEARANCE, CLEAR	FT	FOOT, FEET	NTS	NOT TO SCALE	STD	STANDARD		
CMU	CONCRETE MASONRY UNIT	FT	FOOT, FEET	OD	OUTSIDE DIAMETER	STRGR	STRUTTING		
COL	COLUMN	FT	FOOT, FEET	OF	OUTSIDE FACE	STRG	STRUTTING		
COMP	COMPRESSION	FT	FOOT, FEET	OH	OPPOSITE HAND	STR	STRUTTING		
CONC	CONCRETE	FT	FOOT, FEET	OP	OPPOSITE	STR	STRUTTING		
CONN	CONNECTION, CONNECT	FT	FOOT, FEET	ORIG	ORIGINAL	STR	STRUTTING		
CONSTR	CONSTRUCTION	FT	FOOT, FEET	OSB	ORIENTED STRAND BOARD	STR	STRUTTING		
CONT	CONTINUOUS	FT	FOOT, FEET			STR	STRUTTING		
CONTR	CONTRACTOR	FT	FOOT, FEET			STR	STRUTTING		
C/P	COMPLETE JOINT PENETRATION WELD	FT	FOOT, FEET			STR	STRUTTING		
CTR	CENTER	FT	FOOT, FEET			STR	STRUTTING		
CTB	COUNTERSINK, COUNTERSUNK	FT	FOOT, FEET			STR	STRUTTING		
CU FT	CUBIC FOOT	FT	FOOT, FEET			STR	STRUTTING		



CERRO SAN LUIS GREENWAY

SHEET INDEX, LEGEND & ABBREVIATION



DESIGNED BY	SKY
DRAWN BY	KM / KWA
CHECKED BY	SKY
APPROVED BY	
SCALE	AS NOTED
DATE	JUNE 2, 2022
CITY SPECIFICATION NO.	1000036
PLAN FILE NO. LOCATION	1417-05-CU21
SHEET NO.	S-101



DESIGNED BY

SKY

DRAWN BY:

KM / KWA

CHECKED BY

SKY

APPROVED BY

SCALE:

AS NOTED

DATE:

JUNE 2, 2022

CITY SPECIFICATION NO.

1000036

PLAN FILE NO. LOCATION

14177-05-CU21

SHEET NO.

REQUIRED VERIFICATION AND INSPECTIONS

MASONRY LEVEL 2 QUALITY ASSURANCE MINIMUM TESTS			
PRIOR TO CONSTRUCTION, VERIFY CERTIFICATE OF COMPLIANCE USED IN MASONRY CONSTRUCTION IN ACCORDANCE WITH SPECIFICATION ARTICLE 1.5.5			
VERIFICATION OF SLUMP, FLOW AND VISUAL STABILITY INDEX (VSI) AS DELIVERED TO THE PROJECT SITE IN ACCORDANCE WITH SPECIFICATION ARTICLE 1.5.4.1.4 FOR SET-CONSIDERING GROUT			
VERIFICATION OF f_m AND $f_{m,sp}$ IN ACCORDANCE WITH SPECIFICATION ARTICLE 1.4.8 PRIOR TO CONSTRUCTION, EXCEPT WHERE SPECIFICALLY EXEMPTED BY THIS CODE			
MINIMUM SPECIAL INSPECTION			
INSPECTION TASK	FREQUENCY ^(M)		REFERENCE FOR CRITERIA
	CONT.	PERIODIC	
1. VERIFY COMPLIANCE WITH APPROVED SUBMITTALS		X	Art. 1.5
2. AS MASONRY CONSTRUCTION BEGINS, VERIFY THAT THE FOLLOWING ARE IN COMPLIANCE:			
a. PROPORTIONS OF SITE-PREPARED MORTAR AND ANCHORAGE		X	Art. 2.1, 2.6.8
b. GRADE AND SIZE OF PRESTRESSING TENDONS AND ANCHORAGES		X	Art. 2.4.8, 2.6.8
c. GRADE, TYPE AND SIZE OF REINFORCEMENT, CONNECTORS, ANCHOR BOLTS AND PRESTRESSING TENDONS AND ANCHORAGES		X	Art. 3.4, 3.6A
d. PRESTRESSING TECHNIQUE		X	Art. 3.6.8
e. PROPERTIES OF THIN-BED MORTAR FOR AAC MASONRY	X ^(N)	X ^(N)	Art. 21.C
f. SAMPLE PANEL CONSTRUCTION		X	Art. 1.6.D
3. PRIOR TO GROUTING, VERIFY THAT THE FOLLOWING ARE IN COMPLIANCE:			
a. GROUT SPACE	X		Art. 3.7.D, 3.9.F
b. PLACEMENT OF PRESTRESSING TENDONS AND ANCHORAGES	X	SEC. 10.8, 10.9	Art. 2.4, 3.8
c. PLACEMENT OF REINFORCEMENT, CONNECTORS AND ANCHOR BOLTS	X	SEC. 6.3.1, 6.3.6, 6.3.7	Art. 3.2.E, 3.4
d. PROPORTIONS OF SITE-PREPARED GROUT AND PRESTRESSING GROUT FOR BONDED TENDONS	X		Art. 2.8.8, 2.6.8.1.8
4. VERIFY DURING CONSTRUCTION:			
a. MATERIALS AND PROCEDURES WITH THE APPROVED SUBMITTALS		X	Art. 1.5
b. PLACEMENT OF MASONRY UNITS AND MORTAR JOINT CONSTRUCTION		X	Art. 3.3.8
c. SET AND LOCATION OF STRUCTURAL ELEMENTS		X	Art. 3.3.F
d. TYPE, SIZE AND LOCATION OF ANCHORS, INCLUDING OTHER DETAILS OF ANCHORAGE OF MASONRY TO STRUCTURAL MEMBERS, FRAMES OR OTHER CONSTRUCTION	X	SEC. 1.2.3(e), 6.1.4.3, 6.2.1	
e. WELDING OF REINFORCEMENT	X	SEC. 6.1.6.2	
f. PREPARATION, CONSTRUCTION AND PROTECTION OF MASONRY DURING COLD WEATHER (TEMPERATURE BELOW 40°F) OR HOT WEATHER (TEMPERATURE ABOVE 90°F)	X		Art. 1.8.C, 1.8.D
g. APPLICATION AND MEASUREMENT OF PRESTRESSING FORCE	X		Art. 3.6.8
h. PLACEMENT OF GROUT AND PRESTRESSING GROUT FOR BONDED TENDONS IS IN COMPLIANCE	X		Art. 3.5, 3.6.C
i. PLACEMENT OF AAC MASONRY UNITS AND CONSTRUCTION OF THIN-BED MORTAR JOINTS	X ^(N)	X ^(N)	Art. 3.3.8.3, 3.3.F.1.b
5. OBSERVE PREPARATION OF GROUT SPECIMENS, MORTAR SPECIMENS AND/OR PRIMS		X	Art. 2.6.8.2.a, 2.6.8.2.b, 2.6.8.3, 2.6.8.4
(M) FREQUENCY REFERS TO THE FREQUENCY OF SPECIAL INSPECTION, WHICH MAY BE CONTINUOUS DURING THE TASK LISTED OR PERIODIC DURING THE TASK LISTED, AS DERIVED IN THE TABLE			
(N) REQUIRED FOR THE FIRST 5000 SQ. FT. OF AAC MASONRY			
(C) REQUIRED AFTER THE FIRST 5000 SQ. FT. OF AAC MASONRY			
SOILS CODE TABLE 1705.6			
SPECIAL INSPECTION OR TEST	CONTINUOUS		PERIODIC
1. VERIFY MATERIALS BELOW SHALLOW FOUNDATIONS ARE ADEQUATE TO ACHIEVE THE DESIGN BEARING CAPACITY	---	X	
2. VERIFY EXCAVATIONS ARE EXTENDED TO PROPER DEPTH AND HAVE REACHED PROPER MATERIAL	---	X	
3. PERFORM CLASSIFICATION AND TESTING OF COMPACTED FILL MATERIALS	---	X	
4. VERIFY USE OF PROPER MATERIAL, DENSITIES, AND LIFT THICKNESSES DURING PLACEMENT AND COMPACTION OF COMPACTED FILL	---	X	
5. PRIOR TO PLACEMENT OF COMPACTED FILL, INSPECT SUBGRADE AND VERIFY THAT SITE HAS BEEN PREPARED PROPERLY	---	X	

SHOP FABRICATION

- SHOP FABRICATION REQUIRES SPECIAL INSPECTION IN ACCORDANCE WITH CODE SECTION 1704.2.5. EXCEPTION: SHOP SPECIAL INSPECTIONS ARE NOT REQUIRED WHEN WORK IS DONE ON THE PREMISES OF FABRICATOR REGISTERED AND APPROVED TO PERFORM SUCH WORK IN ACCORDANCE WITH CODE SECTION 1704.2.1.1. THE FOLLOWING ACCREDITATIONS MEET THE REQUIREMENTS OF THE EXCEPTION:
 - STEEL BUILDINGS (OR STEEL ELEMENTS IN OTHER BUILDINGS)
 - FOR GENERAL STEEL BUILDINGS OR ELEMENTS THE FABRICATOR SHALL BE AN AISC CERTIFIED FABRICATOR IN ACCORDANCE WITH THE AISC CERTIFICATION PROGRAM FOR STRUCTURAL STEEL FABRICATORS (AISC 205-06).
 - OTHER ACCREDITATION DEEMED ACCEPTABLE BY THE AUTHORITY HAVING JURISDICTION.
 - IF FABRICATION IS PERFORMED BY AN APPROVED FABRICATOR A CERTIFICATE OF COMPLIANCE MUST BE PROVIDED TO THE BUILDING INSPECTOR THAT THE MATERIALS SUPPLIED AND WORK PERFORMED BY THE FABRICATOR ARE IN CONFORMANCE WITH THE CONSTRUCTION DOCUMENTS.
 - IF FABRICATION IS NOT PERFORMED BY AN APPROVED FABRICATOR WELDING INSPECTION REPORTS MUST BE SUBMITTED TO THE BUILDING OFFICIAL BY AN APPROVED TESTING AGENCY.
 - NONDESTRUCTIVE TESTING (NDT) MAY BE PERFORMED BY THE FABRICATOR, HOWEVER THE QA AGENCY SHALL REVIEW THE FABRICATOR'S NOT REPORTS.
- WOOD BUILDINGS
 - WOOD STRUCTURAL PANELS (SHEATHING) SHALL BE IDENTIFIED BY THE APA TRADEMARK.

REQUIRED VERIFICATION AND INSPECTIONS

CONCRETE CONSTRUCTION CODE TABLE 1705.7				
SPECIAL INSPECTION OR TEST	CONTINUOUS		REFERENCED STANDARD	CIC REFERENCE
		PERIODIC		
1. INSPECT REINFORCEMENT, INCLUDING PRESTRESSING TENDONS, AND VERIFY PLACEMENT:	---	X	ACI 318, CH. 20, 25.2, 25.3, 26.5.1, 26.6.3	1908.4
2. REINFORCING BAR WELDING: - VERIFY WELDABILITY OF REINFORCING BARS OTHER THAN ASTM A706 - INSPECT SINGLE PASS RILEY WELD, MAXIMUM $\frac{1}{2}$" AND - INSPECT ALL OTHER WELDS	---	X	ANSI D1.4, ACI 318-26.5.4	---
3. INSPECT ANCHORS CAST IN CONCRETE	---	X	ACI 318, 17.8.2	---
4. INSPECT ANCHORS POST-INSTALLED IN HARDENED CONCRETE MEMBERS ^(M) - ADHESIVE ANCHORS INSTALLED IN HORIZONTAL OR UPWARDLY INCLINED ORIENTATIONS TO RESIST SUSTAINED TENSION LOADS - MECHANICAL ANCHORS AND ADHESIVE ANCHORS NOT COVERED IN 4.4.	X	ACI 318, 17.8.2.4	---	---
5. VERIFY USE OF REQUIRED MAY DESIGN	---	X	ACI 318, CH. 19, 26.4.3, 26.4.4	1904.L, 1904.2, 1908.2, 1908.3
6. PRIOR TO CONCRETE PLACEMENT, FABRICATE SPECIMENS FOR STRENGTH TESTS, PERFORM SLUMP AND AIR CONTENT TESTS, AND DETERMINE THE TEMPERATURE OF THE CONCRETE	X	---	ASTM C 172, ASTM C 31, ACI 318-26.5, 26.12	1908.10
7. INSPECT CONCRETE AND SHOTCRETE PLACEMENT FOR PROPER APPLICATION TECHNIQUES	X	---	ACI 318-26.5	1908.6, 1908.7, 1908.9
8. VERIFY MAINTENANCE OF SPECIFIED CURING TEMPERATURE AND TECHNIQUES	---	X	ACI 318-26.5.3, 26.5.5	1908.9
9. INSPECT PRESTRESSED CONCRETE FOR: - APPLICATION OF PRESTRESSING FORCES; AND - GROUTING OF BONDED PRESTRESSING TENDONS	X	---	ACI 318-26.10	---
10. INSPECT DIRECTION OF PRECAST CONCRETE MEMBERS	---	X	ACI 318-26.9	---
11. VERIFY IN-SITU CONCRETE STRENGTH PRIOR TO STRESSING OF TENDONS IN POST-TENSIONED CONCRETE AND PRIOR TO REMOVAL OF SHORES AND FORMS FROM BEAMS AND STRUCTURAL SLAB	---	X	ACI 318-26.11.2	---
12. INSPECT FORMWORK FOR BEAMS, LOCATION, AND DIMENSIONS OF THE CONCRETE MEMBER BEING FORMED.	---	X	ACI 318-26.11.1.2 (b)	---
SPECIAL INSPECTIONS LISTED FOR CONCRETE ALSO APPLY TO GROUTING OPERATIONS.				

STATEMENT OF SPECIAL INSPECTIONS


- THIS STATEMENT OF SPECIAL INSPECTIONS HAS BEEN PREPARED PURSUANT TO SECTION 1704.3 OF THE CODE. THIS SECTION DETAILS BOTH REQUIRED SPECIAL INSPECTIONS AND TESTS INCLUDING TESTING PER SECTION 1705 OF THE CODE. THE FOLLOWING SHALL BE OBSERVED DURING THEIR IMPLEMENTATION:
 - GENERAL:
 - STRUCTURAL VERIFICATIONS, INSPECTIONS AND TESTS SHALL BE PERFORMED IN ACCORDANCE WITH CHAPTER 17 OF THE CODE AND/OR THE APPLICABLE REFERENCE STANDARD.
 - OWNER REQUIREMENTS:
 - THE OWNER OR OWNER'S AGENT SHALL EMPLOY ONE OR MORE APPROVED AGENCIES TO PERFORM INSPECTIONS DURING CONSTRUCTION ON THE TYPES OF WORK LISTED IN SECTION 1705 OF THE CODE AND IN THIS STATEMENT OF INSPECTIONS.
 - SPECIAL INSPECTOR QUALIFICATIONS:
 - THE SPECIAL INSPECTIONS SHALL PROVIDE WRITTEN DOCUMENTATION TO THE BUILDING OFFICIAL DEMONSTRATING HIS OR HER COMPETENCE AND RELEVANT EXPERIENCE OR TRAINING. THE EXPERIENCE OR TRAINING SHALL BE CONSIDERED RELEVANT WHEN THE DOCUMENTED EXPERIENCE OR TRAINING IS RELATED IN COMPLIANCE TO THE SAME TYPE OF SPECIAL INSPECTION ACTIVITIES FOR PROJECTS OF SIMILAR COMPLEXITY AND MATERIAL QUANTITIES.
 - CONTRACTOR REQUIREMENTS:
 - SPECIAL INSPECTION IS IN ADDITION TO THE CONTRACTOR'S QUALITY CONTROL INSPECTIONS AND TESTING. THE CONTRACTOR'S QUALITY CONTROL INSPECTIONS AND TESTING SHALL OCCUR PRIOR TO SPECIAL INSPECTION AND REPORTS SHALL BE AVAILABLE TO THE SPECIAL INSPECTOR.
 - THE CONTRACTOR SHALL ENSURE THAT THE WORK FOR WHICH SPECIAL INSPECTION IS REQUIRED REMAINS ACCESSIBLE AND EXPOSED FOR SPECIAL INSPECTION PURPOSES UNTIL COMPLETION OF THE REQUIRED SPECIAL INSPECTION.
 - ANY CONTRACTOR RESPONSIBLE FOR THE CONSTRUCTION OF THE MAIN WIND OR SEISMIC FORCE RESISTING SYSTEM SHALL SUBMIT A WRITTEN STATEMENT OF RESPONSIBILITY TO THE BUILDING OFFICIAL AND OWNER PRIOR TO COMMENCEMENT OF WORK ON THE SYSTEM OR COMPONENT. THE STATEMENT OF RESPONSIBILITY SHALL CONTAIN AN ACKNOWLEDGEMENT OF AWARENESS OF THE SPECIAL INSPECTION REQUIREMENTS CONTAINED IN THE STATEMENT OF SPECIAL INSPECTIONS.
 - SPECIAL INSPECTOR REPORT REQUIREMENTS:
 - THE SPECIAL INSPECTOR SHALL KEEP RECORD OF INSPECTIONS
 - THE SPECIAL INSPECTOR SHALL FURNISH INSPECTION REPORTS TO THE BUILDING OFFICIAL AND TO THE ARCHITECT AND STRUCTURAL ENGINEER OF RECORD.
 - REPORTS SHALL INDICATE THAT WORK INSPECTED WAS OR WAS NOT COMPLETED IN CONFORMANCE TO APPROVED CONSTRUCTION DOCUMENTS.
 - DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE BUILDING OFFICIAL.
 - IF NOT CORRECTED DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE BUILDING OFFICIAL AND THE ARCHITECT AND STRUCTURAL ENGINEER OF RECORD PRIOR TO THE COMPLETION OF THAT PHASE OF WORK.
 - A FINAL REPORT DOCUMENTING SPECIAL INSPECTIONS AND CORRECTION OF ANY DISCREPANCIES NOTED SHALL BE SUBMITTED TO THE BUILDING OFFICIAL.
- SUBMITTALS
 - THE FOLLOWING SUBMITTALS SHALL BE SUBMITTED FOR REVIEW AND APPROVAL BY THE ENGINEER:
 - STEEL INCLUDING MISC. METALS
 - SHOP DRAWINGS FOR FABRICATION AND ERECTION
 - WPS'S (INCLUDING PQPS AS APPLICABLE)
 - REINFORCING STEEL
 - SHOP DRAWINGS FOR FABRICATION AND PLACEMENT
 - BEFORE SUBMITTING EACH SUBMITTAL, (INCLUDING SHOP DRAWINGS, PRODUCT DATA, SAMPLES AND SIMILAR SUBMITTALS), THE CONTRACTOR SHALL HAVE:
 - REVIEWED AND COORDINATED EACH SUBMITTAL WITH OTHER SUBMITTALS AND WITH THE REQUIREMENTS OF THE WORK AND THE CONTRACT DOCUMENTS. THIS INCLUDES THE CONTRACTOR REVIEWING AND VERIFYING THAT THE SUBMITTAL IS COORDINATED AMONG ALL CONSTRUCTION TRADES.
 - DETERMINED AND VERIFIED ALL FIELD MEASUREMENTS, QUANTITIES, DIMENSIONS, SPECIFIED PERFORMANCE AND DESIGN CRITERIA, INSTALLATION REQUIREMENTS, MATERIAL CATALOG NUMBERS AND SIMILAR INFORMATION
 - DETERMINED AND VERIFIED ALL INFORMATION RELATIVE TO THE CONTRACTOR'S RESPONSIBILITIES FOR MEANS, METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES OF CONSTRUCTION, AND SAFETY PRECAUTIONS AND PROGRAMS.
 - REVIEWED AND VERIFIED THAT THE ARCHITECT'S OR ENGINEER'S COMMENTS FROM PREVIOUS SUBMITTAL ROUNDS HAVE BEEN ADDRESSED.
- EACH SUBMITTAL SHALL BEAR A STAMP OR SPECIFIC WRITTEN CERTIFICATION THAT THE CONTRACTOR HAS SATISFIED THEIR OBLIGATIONS UNDER THE CONTRACT DOCUMENTS WITH RESPECT TO THE CONTRACTOR'S REVIEW AND APPROVAL OF THAT SUBMITTAL.
- THE CONTRACTOR'S OBLIGATION TO PERFORM AND COMPLETE THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS SHALL BE ABSOLUTE.
 - REVIEW AND APPROVAL OF SHOP DRAWINGS BY THE ARCHITECT AND/OR ENGINEER DOES NOT CONSTITUTE APPROVAL OF A CHANGE REQUEST, SUBSTITUTION OR MODIFICATION TO THE CONTRACT DRAWINGS.
 - THE ARCHITECT AND ENGINEER SHALL BE NOTIFIED OF CHANGE REQUESTS, SUBSTITUTIONS OR MODIFICATIONS TO THE CONTRACT DRAWINGS IN WRITING BEFORE AND SEPARATE FROM THE SUBMITTAL PRIOR TO SUBMISSION.
- FABRICATION FOR ITEMS IN THESE DOCUMENTS SHALL NOT COMMENCE UNTIL THE SUBMITTAL HAS BEEN REVIEWED AND APPROVED BY THE ENGINEER.




CERRO SAN LUIS GREENWAY
RETAINING WALL DETAILS




DESIGNED BY: SKY
DRAWN BY: KM / KWA
CHECKED BY: SKY
APPROVED BY:
SCALE: AS NOTED
DATE: JUNE 2, 2022
CITY SPECIFICATION NO: 1000036
PLAN FILE NO / LOCATION: 1417-05-CU21
SHEET NO:



h _o	d _{hg}	f _{den} (N)	B	C	W	REIN						S _{min}	S _{max}
						FIG TOP		FIG BOTTOM		WALL			
						T	L	T	L	VERT "Y"	HORIZ "Y"		
2'-0"	12"	8	1'-0"	1'-4"	3'-0"	#5 @ 12"	#4 @ 16"	#5 @ 12"	#4 @ 16"	#5 @ 12"	#4 @ 24"	8"	2'-4"



h _a	d _b	k	f _{max} (N)	B	C	W	REIN						S _{min}	S _{max}
							FIG TOP		FIG BOTTOM		WALL			
							T	L	T	L	VERT "V"	HORIZ "H"		
5'-6"	18"	12"	12	1'-0"	1'-4"	3'-0"	#6 @ 12"	#4 @ 12"	#6 @ 12"	#4 @ 12"	#5 @ 12"	#4 @ 24"	6"	5'-6"



REIN'																	
No.	d _{min}	f _y	f _{min} (%)	B	C	W	FIG TOP				FIG BOTTOM				f _{min} MIN	f _{min} MAX	Ø
							T	L	T	L	T	L	VERT. Y	HORIZ. Y			
3-0'	12"	N/A	8	0-4'	1-4'	3-0'	16.0 12"	15.0 16"	16.0 12"	15.0 16"	15.0 12"	14.0 24"	8"	2-0'	0		
3-0'	12"	N/A	8	1-4'	1-4'	1-4'	16.0 12"	15.0 16"	16.0 12"	15.0 16"	15.0 12"	14.0 24"	8"	2-0'	0		
7-0'	12"	8	8	2-0'	1-4'	4-0'	16.0 12"	15.0 16"	16.0 12"	15.0 16"	15.0 12"	14.0 24"	12"	6-0'	0		

51

41

52

42

LANDSCAPE HIGH CURB

1/2" ± 1/4"

32

RAMONA STORMWATER WALL


1/2" ± 1/4"

22

BIKE PATH CONCRETE WALL @ PROP LINE

1/2" ± 1/4"



12



POST @ CONC WALL

1/2" ± 1/4"

33



53

43

54

44

CURB AND GUTTER WALL

1/2" ± 1/4"

24

BIKE PATH CONCRETE WALL

1/2" ± 1/4"

14